

GLAH14 Product Data Dictionary

File-Level (Global) Attributes

Attribute	Example Value
featureType	timeSeries
ShortName	GLAH14
title	GLAS/ICESat L2 Global Land Surface Altimetry Data (HDF5)
comment	GLAH14 contains the land elevation and elevation distribution corrected for geodetic and atmospheric affects calculated from algorithms fine-tuned for over land returns. Data granules contain 14 orbits of data within the land mask.
summary	GLAH14 contains GLAS land elevation data that includes geolocation and reflectance plus the geodetic, instrument, and atmospheric corrections used. Parameters are at the full 40Hz resolution for locations that fall within the ICESat land mask. Each GLAH14 file was created from an equivalent GLA14 binary file. The data used to create the GLAH14 values are contained in the equivalent GLAHxx files for the GLAxx files. See the provenance metadata for the creation of the GLA14.
license	https://nsidc.org/data/icesat/disclaimer.html
references	https://nsidc.org/data/glah01-glah05-glah06-glah12-glah13-glah14-glah15/versions/34/documentation (Guide Document for this product at NSIDC), https://nsidc.org/data/icesat/ (GLAS Product page at NSIDC)
AccessConstraints	Data may not be reproduced or distributed without including the CitationForExternalPublication for this product included in this Metadata. Data may not be distributed in an altered form without the written permission of the GLAS Science Team.
CitationforExternalPublication	The data used in this study were produced by the GLAS Science Team at the ICESat Science Investigator-led Processing System (I-SIPS) at NASA/GSFC. The data archive site is the NSIDC DAAC.
contributor_role	Data Originator, Investigator, Producer, Producer
contributor_name	David W. Hancock (David.W.Hancock@nasa.gov), Bob E Schutz (schutz@utcsr.ae.utexas.edu), Jay Zwally (Jay.Zwally@nasa.gov), John P DiMarzio (John.P.Dimarzio.1@nasa.gov)
creator_name	ICESat Science Investigator-led Processing System (I-SIPS)
creator_email	David.W.Hancock@nasa.gov
publisher_name	NSIDC User Services
publisher_email	nsidc@nsidc.org
publisher_url	https://nsidc.org/data/icesat/
platform	Ice, Cloud, and Land Elevation Satellite (ICESat)
instrument	Geoscience Laser Altimeter System (GLAS)
processing_level	2

Attribute	Example Value
date_created	2014-08-18T21:11:22
spatial_coverage_type	Horizontal
history	2014-05-24T04:16:41 glas_alt 6.1 GLA14_634_2103_002_0407_0_01_0001.DAT, 2014-08-18T21:11:22.000000Z GLA14_h5_convert Version 1.4 (July 2014) /GLAH14_634_2103_002_0407_0_01_0001.H5
geospatial_lat_min	-90.0
geospatial_lat_max	90.0
geospatial_lon_min	-180.0
geospatial_lon_max	180.0
geospatial_lat_units	degrees_north
geospatial_lon_units	degrees_east
keywords	Earth Science > Land Surface > Topography > Terrain Elevation > Laser Reflectance, Earth Science > Land Surface > Surface Radiative Properties > Reflectance > Laser Reflectance
keywords_vocabulary	GCMD Science Keywords Version 6.0
standard_name_vocabulary	not_set
naming_authority	http://dx.doi.org/10.5067/ICESAT/GLAS/DATA211
project	Ice, Cloud, and Land Elevation Satellite (GLAS_HDF)
time_type	UTC
date_type	J2000
time_coverage_start	2003-11-18T01:51:38
time_coverage_end	2003-11-19T00:24:44
time_coverage_duration	81280
source	Satellite Measurements
HDFVersion	HDF5 1.8.9
identifier_file_uuid	2e672450-982e-43a3-ad9a-65c360d51ad4
identifier_product_doi	10.5067/ICESAT/GLAS/DATA211
identifier_product_type	GLAH14
identifier_product_format_version	1.0
Conventions	CF-1.6
institution	National Aeronautics and Space Administration (NASA)

Group: /Data_1HZ

This group contain data with a rate of 1HZ. 1Hz data may be indexed to the 40HZ data using the `i_rec_ndx` parameter in each respective time group.

Dimension Scales

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
<code>DS_UTCTime_1</code>	DOUBLE (UNLIMITED)	Transmit Time of First Shot in frame in J2000 (time)	seconds since 2000-01-01 12:00:00 UTC	The transmit time of the first shot in the 1 second frame measured as UTC seconds elapsed since Jan 1 2000 12:00:00 UTC. This time has been derived from the GPS time accounting for leap seconds.	Rel 34 GLAS Binary Data	NOT_SET

Group: Data_1HZ/Time

This group contains the 1HZ index and time-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
<code>i_rec_ndx</code>	INTEGER (UNLIMITED)	GLAS Record Index (NOT_SET)	NOT_SET	Unique index that relates this record to the corresponding record(s) in each GLAS data product.	Rel 34 GLAS Binary Data	DS_UTCTime_1				
<code>i_shot_count</code>	INTEGER (UNLIMITED)	GLAS shot counter (NOT_SET)	NOT_SET	Identifies each laser shot within a record index. A combination of <code>i_rec_ndx</code> and <code>i_shot_count</code> can be used to uniquely identify each GLAS laser shot.	Rel 34 GLAS Binary Data	DS_UTCTime_1				
<code>d_transtime</code>	DOUBLE (UNLIMITED)	One way transit time (NOT_SET)	seconds	One way transit time calculated using the preliminary range offset. This is added to the UTC time tag to get the ground bounce times at which to calculate the orbit	Rel 34 GLAS Binary Data	DS_UTCTime_1				
<code>d_deltagpstmcor</code>	DOUBLE (UNLIMITED)	Delta GPS time correction (NOT_SET)	seconds	The high frequency delta GPS time correction calculated during the precision orbit processing step.	Rel 34 GLAS Binary Data	DS_UTCTime_1				
<code>shot_time_flg</code>	INTEGER_1 (UNLIMITED)	time correction flag (NOT_SET)	NOT_SET	Shot time flag; Indicates what shot time is used. <table border="1" data-bbox="812 1522 1237 1711"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>transmit_time ground_bounce_time</td> </tr> </table>	flag values	flag_meanings	0, 1	transmit_time ground_bounce_time	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	transmit_time ground_bounce_time									
<code>gps_time_flg</code>	INTEGER_1 (UNLIMITED)	time correction flag (NOT_SET)	NOT_SET	GPS time flag; Indicates if delta gps time correction is applied to shot time. <table border="1" data-bbox="812 1837 1214 1969"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>not_applied applied</td> </tr> </table>	flag values	flag_meanings	0, 1	not_applied applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	not_applied applied									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
p1_timing_flg	INTEGER_1 (UNLIMITED)	time correction flag (NOT_SET)	NOT_SET	Post-launch timing; indicates if post-launch timing bias is applied. Data value is stored in the Metadata group. <table border="1" data-bbox="812 304 1214 441"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>not_applied applied</td> </tr> </table>	flag values	flag_meanings	0, 1	not_applied applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	not_applied applied									
ddelay_flg	INTEGER_1 (UNLIMITED)	time correction flag (NOT_SET)	NOT_SET	Digitizer turn-on delay flag; Indicates if digitizer turn-on delay is accounted for in shot time. Data value is stored in the Metadata group. <table border="1" data-bbox="812 588 1214 724"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
peaktp_flg	INTEGER_1 (UNLIMITED)	time correction flag (NOT_SET)	NOT_SET	Peak of transmit pulse flag; Indicates if time to peak of transmit pulse is accounted for in shot time. <table border="1" data-bbox="812 871 1214 1008"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									

Group: Data_1HZ/Geolocation

This group contains geolocation-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_lat	DOUBLE (UNLIMITED)	Spot 1 Coordinate Data, Latitude Corrected (latitude)	degrees_north	The geodetic latitude of the laser spot computed from the precision orbit, precision attitude, and ice-sheet specific range after instrument corrections, atmospheric delays and tides have been applied. The values are in degrees north.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_lon	DOUBLE (UNLIMITED)	Spot 1 Coordinate Data, Longitude Corrected (longitude)	degrees_east	The longitude of the laser spot computed from the precision orbit, precision attitude, and ice-sheet specific range after instrument corrections, atmospheric delays and tides have been applied. The values are in degrees east.	Rel 34 GLAS Binary Data	DS_UTCTime_1
i_track	INTEGER (UNLIMITED)	i_track (NOT_SET)	NOT_SET	The track number.	Rel 34 GLAS Binary Data	DS_UTCTime_1

Group: Data_1HZ/Packet_data

This group contains flags indicating packet availability.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
apid_ADLg_1_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer large wf packet APID availability flag for 1st 10 shots <table border="1" data-bbox="812 273 1274 472"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADLg_2_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer large wf packet APID availability flag for 2nd 10 shots <table border="1" data-bbox="812 588 1274 787"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADLg_3_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer large wf packet APID availability flag for 3rd 10 shots <table border="1" data-bbox="812 903 1274 1102"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADLg_4_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer large wf packet APID availability flag for 4th 10 shots <table border="1" data-bbox="812 1218 1274 1417"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADSm_1_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer small wf packet APID availability flag for 1st 10 shots <table border="1" data-bbox="812 1533 1274 1732"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
apid_ADSm_2_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer small wf packet APID availability flag for 2nd 10 shots <table border="1" data-bbox="812 273 1271 468"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADSm_3_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer small wf packet APID availability flag for 3rd 10 shots <table border="1" data-bbox="812 594 1271 789"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADSm_4_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer small wf packet APID availability flag for 4th 10 shots <table border="1" data-bbox="812 915 1271 1110"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_PC532_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	532 Photon counter packet APID availability flag <table border="1" data-bbox="812 1194 1271 1390"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_CD1064_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	1064 Cloud Digitizer packet APID availability flag <table border="1" data-bbox="812 1474 1271 1669"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ADSci_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Ancillary science packet APID availability flag <table border="1" data-bbox="812 1753 1271 1948"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
apid_ASAD_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Altimeter Digitizer telemetry data in Ancillary science packet APID availability flag <table border="1" data-bbox="812 273 1271 468"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ASPC_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Photon counter telemetry data in Ancillary science packet APID availability flag <table border="1" data-bbox="812 594 1271 789"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ASCF_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Cloud Digitizer telemetry data in Ancillary science packet APID availability flag <table border="1" data-bbox="812 915 1271 1110"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_ASCT_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	C&T board telem. data in Ancillary science packet APID availability flag <table border="1" data-bbox="812 1236 1271 1432"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_CT20_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	CT HW telemetry packet #1 (APID 20) APID availability flag <table border="1" data-bbox="812 1558 1271 1753"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
apid_CT21_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	CT HW telemetry packet #2 (APID 21) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_CT22_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	CT HW telemetry packet #3 (APID 22) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_CT23_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	CT HW telemetry packet #4 (APID 23) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_CT50_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	CT HW telemetry packet #5 (APID 50) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_SS24_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Small software telemetry packet #1 (APID 24) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
apid_LS25_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Large software telemetry packet #1 (APID 25) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_LS55_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	Large software telemetry packet #2 (APID 55) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_GPS_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	GPS telemetry packet APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_PRAP_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	S/C position, rate, and attitude telemetry packet (PRAP) APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_LPA_1_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	LPA packet #1 APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_LPA_2_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	LPA packet #2 APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
apid_LPA_3_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	LPA packet #3 APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									
apid_LPA_4_flg	INTEGER_1 (UNLIMITED)	APID Data Availability Flag (NOT_SET)	NOT_SET	LPA packet #4 APID availability flag <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>present filled_at_EDOS never_received_ISIPS_filled</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled	Rel 34 GLAS Binary Data	DS_UTCTime_
flag values	flag_meanings									
0, 1, 2	present filled_at_EDOS never_received_ISIPS_filled									

Group: Data_1HZ/Quality

This group contains quality-related parameters and flags.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source				
orbit_pred_flg	INTEGER_1 (UNLIMITED)	POD flag (Orbit Flag) (NOT_SET)	NOT_SET	Predicted or precision orbit flag. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>precision_orbit_used predicted_orbit_used onboard_orbit_used</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	precision_orbit_used predicted_orbit_used onboard_orbit_used	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1, 2	precision_orbit_used predicted_orbit_used onboard_orbit_used								
orbit_man_flg	INTEGER_1 (UNLIMITED)	POD flag (Orbit Flag) (NOT_SET)	NOT_SET	Maneuver flag. If maneuvers occurred orbit is considered degraded. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_maneuvers maneuvers_occurred_during_this_record</td> </tr> </table>	flag values	flag_meanings	0, 1	no_maneuvers maneuvers_occurred_during_this_record	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	no_maneuvers maneuvers_occurred_during_this_record								
orbit_model_flg	INTEGER_1 (UNLIMITED)	POD flag (Orbit Flag) (NOT_SET)	NOT_SET	Model problems flag. <code>model_problems</code> indicated when orbit RMS > 5 cm; indicates required accuracy not met. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_model_problems model_problems</td> </tr> </table>	flag values	flag_meanings	0, 1	no_model_problems model_problems	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	no_model_problems model_problems								

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source				
orbit_att_flg	INTEGER_1 (UNLIMITED)	POD flag (Orbit Flag) (NOT_SET)	NOT_SET	Attitude flag; modeled_attitude_used indicates possible orbit degradation. <table border="1" data-bbox="824 275 1401 468"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>instrument_attitude_used_for_orbit modeled_attitude_used</td> </tr> </table>	flag values	flag_meanings	0, 1	instrument_attitude_used_for_orbit modeled_attitude_used	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	instrument_attitude_used_for_orbit modeled_attitude_used								
orbit_array_flg	INTEGER_1 (UNLIMITED)	POD flag (Orbit Flag) (NOT_SET)	NOT_SET	Solar ray orientation flag; modeled_solar_ray_orientation indicates possible orbit degradation. <table border="1" data-bbox="824 594 1401 810"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>solar_ray_orientation_used_from measurement modeled_solar_ray_orientation</td> </tr> </table>	flag values	flag_meanings	0, 1	solar_ray_orientation_used_from measurement modeled_solar_ray_orientation	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	solar_ray_orientation_used_from measurement modeled_solar_ray_orientation								
orbit_gps_flg	INTEGER_1 (UNLIMITED)	POD flag (Orbit Flag) (NOT_SET)	NOT_SET	GPS flag; GPS_data_missing indicates GPS data missing from portion of this record and possible degradation. <table border="1" data-bbox="824 936 1401 1129"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_GPS_data_outage GPS_data_missing</td> </tr> </table>	flag values	flag_meanings	0, 1	no_GPS_data_outage GPS_data_missing	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	no_GPS_data_outage GPS_data_missing								
att_offnadir_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	Off-nadir angle flag; Indicates if off-nadir angle is within limits. <table border="1" data-bbox="824 1224 1320 1360"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>within_limit outside_limits</td> </tr> </table>	flag values	flag_meanings	0, 1	within_limit outside_limits	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	within_limit outside_limits								
att_oceansw_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	Ocean sweep flag; Indicates if an ocean sweep is within the time frame of this record. <table border="1" data-bbox="824 1486 1320 1623"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>not_ocean_sweep ocean_sweep</td> </tr> </table>	flag values	flag_meanings	0, 1	not_ocean_sweep ocean_sweep	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	not_ocean_sweep ocean_sweep								
att_pointing_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	Target of opportunity off-pointing flag; Indicates if this record is within time of target of opportunity off-pointing. <table border="1" data-bbox="824 1749 1250 1885"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>not_pointing pointing</td> </tr> </table>	flag values	flag_meanings	0, 1	not_pointing pointing	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	not_pointing pointing								

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source				
att_steering_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	Steering to reference <code>i_track</code> flag; Indicates if this record is within target of opportunity off-pointing. <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1</td> <td>not_pointing pointing</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1	not_pointing pointing	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	not_pointing pointing								
att_actual_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	Actual data bits flag; Indicates if the first 3 Attitude Flags have been set based on actual data, if ignore, then IGNORE those bits. <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1</td> <td>actual ignore</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1	actual ignore	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	actual ignore								
att_ist_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	IST data flag; Indicates if IST data are good, missing for at least a portion of the time of this frame, noisy for at least a portion of the time of this frame or noisy and missing for at least a portion of the time of this frame. <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3</td> <td>good missing noisy missing_noisy</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3	good missing noisy missing_noisy	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1, 2, 3	good missing noisy missing_noisy								
att_gyro_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	GYRO data flag; Indicates if GYRO data are good, missing for at least a portion of the time of this frame, noisy for at least a portion of the time of this frame or noisy and missing for at least a portion of the time of this frame. <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3</td> <td>good missing noisy missing_noisy</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3	good missing noisy missing_noisy	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1, 2, 3	good missing noisy missing_noisy								
att_lrs_flg	INTEGER_1 (UNLIMITED)	Attitude Flag 1 (NOT_SET)	NOT_SET	LRS Data flag; Indicates the following conditions: LRS data good, consists of star, laser and CRS; LRS data good, but no star data for at least a portion of this frame; LRS data good, but no laser data for at least a portion of this frame; LRS data good, but no CRS data for at least a portion of this frame; LRS data good, but only CRS data for at least a portion of this frame; LRS data good, but only laser data for at least a portion of this frame; LRS data good, but only star data for at least a portion of this frame; Missing LRS for at least a portion of the time of this frame. <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3, 4, 5, 6, 7</td> <td>good no_star no_laser no_crs only_crs only_laser only_star missing_lrs</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3, 4, 5, 6, 7	good no_star no_laser no_crs only_crs only_laser only_star missing_lrs	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1, 2, 3, 4, 5, 6, 7	good no_star no_laser no_crs only_crs only_laser only_star missing_lrs								

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source				
altfrm_corr_flg	INTEGER_1 (UNLIMITED)	Altimeter Frame Quality Flag (NOT_SET)	NOT_SET	<p>Corrections flag; Indicates if all data in frame are good with appropriate corrections applied; or if some of data are not corrected or have measurement problems.</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>good uncorrected</td> </tr> </table>	flag values	flag_meanings	0, 1	good uncorrected	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	good uncorrected								
altfrm_data_flg	INTEGER_1 (UNLIMITED)	Altimeter Frame Quality Flag (NOT_SET)	NOT_SET	<p>Frame data flag; Indicates if there are at least some usable data in the frame; or if all elevations in the frame are bad due to problems with corrections.</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>good not_good</td> </tr> </table>	flag values	flag_meanings	0, 1	good not_good	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	good not_good								
altfrm_meas_flg	INTEGER_1 (UNLIMITED)	Altimeter Frame Quality Flag (NOT_SET)	NOT_SET	<p>Measurements flag; Indicates if all GLAS measurements are good or if there is at least one unusable measurement in the frame.</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>good not_good</td> </tr> </table>	flag values	flag_meanings	0, 1	good not_good	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	good not_good								
altfrm_use_flg	INTEGER_1 (UNLIMITED)	Altimeter Frame Quality Flag (NOT_SET)	NOT_SET	<p>Usable Measurements flag; Indicates if there is at least one usable measurement in the frame; or if all GLAS measurements are bad.</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>usable not_usable</td> </tr> </table>	flag values	flag_meanings	0, 1	usable not_usable	Rel 34 GLAS Binary Data
flag values	flag_meanings								
0, 1	usable not_usable								

Group: Data_1HZ/Transmit_Energy

This group contains parameters related to transmit energy.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_tpazimuth_avg	DOUBLE (UNLIMITED)	Transmit Pulse azimuth - frame avg (NOT_SET)	degrees	Transmit pulse azimuth. Average over the 1-second frame. Angle eastwards from north of the major axis of the transmit pulse, as seen by the LPA. From ANC09.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_tpeccentricity_avg	DOUBLE (UNLIMITED)	Transmit Pulse eccentricity - frame avg (NOT_SET)	NOT_SET	Transmit pulse eccentricity as measured by the LPA. Averaged over the 1-second frame. From ANC09.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_tpmajoraxis_avg	DOUBLE (UNLIMITED)	Transmit Pulse major axis - frame avg (NOT_SET)	meters	Trasmit pulse major axis as measured by the LPA. Averaged over the 1-second time frame. From ANC09.	Rel 34 GLAS Binary Data	DS_UTCTime_1

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_tpintensity_avg	DOUBLE (UNLIMITED)	Transmit Pulse intensity - frame avg (NOT_SET)	count	Transmit pulse intensity as measured by the LPA. Averaged over the 1-second frame. From ANC09.	Rel 34 GLAS Binary Data	DS_UTCTime_1

Group: Data_1HZ/Reflectivity

This group contains reflectivity information.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_localSolarTime	DOUBLE (UNLIMITED)	Local apparent solar time (NOT_SET)	seconds	Local apparent solar time.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_Azimuth	DOUBLE (UNLIMITED)	Local Azimuth (solar_azimuth_angle)	degrees	Mean azimuth measured clockwise from north based on latitude, longitude, and elevation of a 1 second interval of the trace of the ground footprint-center.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_solAng	DOUBLE (UNLIMITED)	Solar Angle (NOT_SET)	degrees	Solar Angle above or below the plane tangent to the ellipsoid surface at the laser spot. Positive values mean the sun is above the horizon, while negative values mean it is below the horizon. The effect of atmospheric refraction is not included. This is a low-precision value, with approximately one degree accuracy.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_reflCor_atm	DOUBLE (UNLIMITED)	Reflectivity Correction Factor For Atmospheric Effects (NOT_SET)	NOT_SET	This reflectance correction factor is calculated as $1 / e^{-(2(tc+ta+tp+tm))}$, where tc is the cloud (column) integrated optical depth, ta is the aerosol (column) integrated optical depth, tp is the planetary boundary layer optical depth, and tm is the molecular optical depth. tm is a constant equal to $-\log(gd_T_RTatm)/2$, where $gd_T_RTatm = 0.98$ is defined in <code>const_elev_mod.f90</code> or read from ANC07-03. The attenuation correction factor has been corrected for multiple scattering. The reflectance has been corrected for waveform saturation.	Rel 34 GLAS Binary Data	DS_UTCTime_1

Group: Data_1HZ/Elevation_Flags

This group contains flags indicating the quality or suitability of elevation data.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
surf_ld_flg	INTEGER_1 (UNLIMITED)	Region Type (NOT_SET)	NOT_SET	Region type flag; indicates presence of Land <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_land land</td> </tr> </table>	flag values	flag_meanings	0, 1	no_land land	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	no_land land									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
surf_si_flg	INTEGER_1 (UNLIMITED)	Region Type (NOT_SET)	NOT_SET	Region type Sea Ice flag; indicates the presence of sea ice. <table border="1" data-bbox="812 273 1201 409"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_sea_ice sea_ice</td> </tr> </table>	flag values	flag_meanings	0, 1	no_sea_ice sea_ice	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	no_sea_ice sea_ice									
surf_oc_flg	INTEGER_1 (UNLIMITED)	Region Type (NOT_SET)	NOT_SET	Region type ocean flag; indicates the presence of ocean. <table border="1" data-bbox="812 535 1153 672"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_ocean ocean</td> </tr> </table>	flag values	flag_meanings	0, 1	no_ocean ocean	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	no_ocean ocean									
surf_is_flg	INTEGER_1 (UNLIMITED)	Region Type (NOT_SET)	NOT_SET	Region type Ice Sheet flag; indicates the presence of ice sheet. <table border="1" data-bbox="812 798 1234 987"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>no_ice_sheet ice_sheet</td> </tr> </table>	flag values	flag_meanings	0, 1	no_ice_sheet ice_sheet	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	no_ice_sheet ice_sheet									
rng_ldtide_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	Load tides flag; Indicates if a correction for the dynamic effect of load tides has been applied to the range before the elevation was calculated. <table border="1" data-bbox="812 1144 1209 1270"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
rng_octide_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	Ocean tides flag; Indicates if a correction for the dynamic effect of ocean tides has been applied to the range before the elevation was calculated. <table border="1" data-bbox="812 1428 1209 1564"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
rng_setide_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	Solid earth tides flag; Indicates if a correction for the dynamic effect of solid earth tides has been applied to the range before the elevation was calculated. <table border="1" data-bbox="812 1743 1209 1879"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
rng_drytrop_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	<p>Dry troposphere flag; Indicates if a correction for propagation errors due to the dry troposphere was applied to the range before the elevation was calculated.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
rng_wettrop_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	<p>Wet troposphere flag Indicates if a correction for propagation errors due to the wet troposphere was applied to the range before the elevation was calculated.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
rng_intbias_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	<p>Internal range bias flag; Indicates if the internal range bias was applied to the range before the elevation was calculated and if the value of d_refRng on the record has this correction applied.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
rng_plbias_flg	INTEGER_1 (UNLIMITED)	Range Correction Flag (NOT_SET)	NOT_SET	<p>Post-launch range bias flag; Indicates if the post-launch range bias was applied to the range before the elevation was calculated and if the value of d_refRng on the record has this correction applied.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1</td> <td>applied not_applied</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1	applied not_applied	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	applied not_applied									
rng_model_flg	INTEGER_1 (UNLIMITED)	Correction Status Flag (NOT_SET)	NOT_SET	<p>Geophysical corrections flag; Indicates if the load and ocean tides are from global model, regional model no. 1, regional model no. 2, or regional model no. 3.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3</td> <td>global model_1 model_2 model_3</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3	global model_1 model_2 model_3	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1, 2, 3	global model_1 model_2 model_3									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
rng_oldmet_flg	INTEGER_1 (UNLIMITED)	Correction Status Flag (NOT_SET)	NOT_SET	<p>Geophysical corrections flag; Indicates if troposphere corrections are based on 6hr NCEP grids surrounding data, 6hr NCEP grids but at least one was >6 but <24 hrs away from data, standard atm, or reanalyzed met data.</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2, 3</td> <td>6_hour over_6_hour standard_atm reanalyzed</td> </tr> </table>	flag values	flag_meanings	0, 1, 2, 3	6_hour over_6_hour standard_atm reanalyzed	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1, 2, 3	6_hour over_6_hour standard_atm reanalyzed									
rng_atmcorr_flg	INTEGER_1 (UNLIMITED)	Correction Status Flag (NOT_SET)	NOT_SET	<p>Geophysical corrections flag; Indicates values used to calculate corrected reflectivity - computed aerosol and cloud optical depths used, default-null aerosol and computed cloud optical depths, computed aerosol and default-null cloud optical depths, default-null values for aerosol and cloud optical depths, or if maximum bound set.</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2, 3, 4</td> <td>computed_only_od only_aerosol defaults max_bound_set</td> </tr> </table>	flag values	flag_meanings	0, 1, 2, 3, 4	computed_only_od only_aerosol defaults max_bound_set	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1, 2, 3, 4	computed_only_od only_aerosol defaults max_bound_set									

Group: Data_1HZ/Atmosphere

This group contains the 1 hz information relating to the atmosphere.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
atm_gla11_flg	INTEGER_1 (UNLIMITED)	Atmosphere Availability Flag (NOT_SET)	NOT_SET	<p>GLA11 data availability flag</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>available not_available</td> </tr> </table>	flag values	flag_meanings	0, 1	available not_available	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	available not_available									
atm_gla09_flg	INTEGER_1 (UNLIMITED)	Atmosphere Availability Flag (NOT_SET)	NOT_SET	<p>GLA09 data availability flag</p> <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>available not_available</td> </tr> </table>	flag values	flag_meanings	0, 1	available not_available	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings									
0, 1	available not_available									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
atm_char_flag	INTEGER_1 (UNLIMITED)	Atmosphere Characterization Flag (NOT_SET)	NOT_SET	<p>Flag to characterize cloud and blowing snow state of the atmosphere based on combinations of <code>hi_cloud</code> (> 5 km), <code>mid_cloud</code> (>2, <=5 km), <code>low_cloud</code> (> 500 m, <=2 km), blowing snow or fog and hi/lo optical depth.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3, 4, 5, 6, 7, 8</td> <td>clear hi_cloud_low_od hi_cloud_high_od mid_cloud_low_od mid_cloud_hi_od low_cloud_low_od low_cloud_hi_od blowing_snow_low_od blowing_snow_hi_od</td> </tr> </tbody> </table>	flag values	flag meanings	0, 1, 2, 3, 4, 5, 6, 7, 8	clear hi_cloud_low_od hi_cloud_high_od mid_cloud_low_od mid_cloud_hi_od low_cloud_low_od low_cloud_hi_od blowing_snow_low_od blowing_snow_hi_od	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag meanings									
0, 1, 2, 3, 4, 5, 6, 7, 8	clear hi_cloud_low_od hi_cloud_high_od mid_cloud_low_od mid_cloud_hi_od low_cloud_low_od low_cloud_hi_od blowing_snow_low_od blowing_snow_hi_od									
atm_char_conf	INTEGER_1 (UNLIMITED)	Atmosphere Characterization Flag Confidence (NOT_SET)	NOT_SET	<p>Confidence level ascribed to the atmosphere characterization flag. 0=not applicable (for contamination flag values of 9 or 10). 1: low confidence. 2: reasonable confidence. 3: high confidence. 10: data quality insufficient to assign flag.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3, 10</td> <td>not_applicable low_confidence reasonable_confidence high_confidence quality_insufficient</td> </tr> </tbody> </table>	flag values	flag meanings	0, 1, 2, 3, 10	not_applicable low_confidence reasonable_confidence high_confidence quality_insufficient	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag meanings									
0, 1, 2, 3, 10	not_applicable low_confidence reasonable_confidence high_confidence quality_insufficient									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates																																
cld1_mswf_flg	INTEGER_1 (UNLIMITED)	Cloud Multiple Scattering Warning Flag (NOT_SET)	NOT_SET	<p>The multiple scattering warning flag (MSWF) is based on the total column optical depth (aerosol plus cloud) calculated in GLA11 using 532nm. It is intended as a way to quickly obtain information about the potential severity of multiple scattering with regards to the range-to-surface calculated by the altimetry processing software. The multiple scattering warning flag will have values ranging from 0-14, based on the total column optical depth. A warning flag value of 15 will signify invalid. An invalid will be encoded if an optical depth in any of the layers in the 1-second column could not be calculated. This usually occurs in a very optically thick cloud which extinguishes the signal. It could also occur if the extinction-to-backscatter ratio assignment is set too high, causing the transmission calculations in the lidar inversion to go out-of-range.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr><td>0, 1,</td><td>under_0.010</td></tr> <tr><td>2, 3,</td><td>0.010_0.030</td></tr> <tr><td>4, 5,</td><td>0.030_0.060</td></tr> <tr><td>6, 7,</td><td>0.060_0.100</td></tr> <tr><td>8, 9,</td><td>0.100_0.150</td></tr> <tr><td>10,</td><td>0.150_0.225</td></tr> <tr><td>11,</td><td>0.225_0.300</td></tr> <tr><td>12,</td><td>0.300_0.400</td></tr> <tr><td>13,</td><td>0.400_0.500</td></tr> <tr><td>14, 15</td><td>0.500_0.670</td></tr> <tr><td></td><td>0.670_0.900</td></tr> <tr><td></td><td>0.900_1.200</td></tr> <tr><td></td><td>1.200_1.600</td></tr> <tr><td></td><td>1.600_2.000</td></tr> <tr><td></td><td>over_2.000 invalid</td></tr> </tbody> </table>	flag values	flag_meanings	0, 1,	under_0.010	2, 3,	0.010_0.030	4, 5,	0.030_0.060	6, 7,	0.060_0.100	8, 9,	0.100_0.150	10,	0.150_0.225	11,	0.225_0.300	12,	0.300_0.400	13,	0.400_0.500	14, 15	0.500_0.670		0.670_0.900		0.900_1.200		1.200_1.600		1.600_2.000		over_2.000 invalid	Rel 34 GLAS Binary Data	DS_UTCTime_1
flag values	flag_meanings																																					
0, 1,	under_0.010																																					
2, 3,	0.010_0.030																																					
4, 5,	0.030_0.060																																					
6, 7,	0.060_0.100																																					
8, 9,	0.100_0.150																																					
10,	0.150_0.225																																					
11,	0.225_0.300																																					
12,	0.300_0.400																																					
13,	0.400_0.500																																					
14, 15	0.500_0.670																																					
	0.670_0.900																																					
	0.900_1.200																																					
	1.200_1.600																																					
	1.600_2.000																																					
	over_2.000 invalid																																					
MRC_af_flg	INTEGER_1 (UNLIMITED)	Medium Resolution Cloud Availability Flag (NOT_SET)	NOT_SET	<p>Indicates number of cloud layers at medium resolution from the 532 nm channel; not_searched = cloud layers were not searched for; not_detected = cloud layers were searched for, but not detected.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr><td>0, 1, 2, 3, 4,</td><td>not_searched 1 2</td></tr> <tr><td>5, 6, 7, 8, 9,</td><td>3 4 5 6 7 8 9 10</td></tr> <tr><td>10, 11, 12,</td><td>11 12 13 14</td></tr> <tr><td>13, 14, 15</td><td>not_detected</td></tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3, 4,	not_searched 1 2	5, 6, 7, 8, 9,	3 4 5 6 7 8 9 10	10, 11, 12,	11 12 13 14	13, 14, 15	not_detected	Rel 34 GLAS Binary Data	DS_UTCTime_1																						
flag values	flag_meanings																																					
0, 1, 2, 3, 4,	not_searched 1 2																																					
5, 6, 7, 8, 9,	3 4 5 6 7 8 9 10																																					
10, 11, 12,	11 12 13 14																																					
13, 14, 15	not_detected																																					
d_Surface_pres	DOUBLE (UNLIMITED)	Surface Pressure (surface_temperature)	hPa	<p>Atmospheric pressure at Earth's surface level measured in hPa and derived from the meteorological data files. This surface pressure is computed in the atmospheric processing and is not the pressure used for the troposphere delay correction.</p>	Rel 34 GLAS Binary Data	DS_UTCTime_1																																

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_Surface_relh	DOUBLE (UNLIMITED)	Relative Humidity (surface_air_pressure)	percent	Atmospheric relative humidity at Earth's surface level measured as a percentage and derived from the meteorological data files.	Rel 34 GLAS Binary Data	DS_UTCTime_1
d_Surface_temp	DOUBLE (UNLIMITED)	Surface Temperature (relative_humidity)	degree Celsius	Atmospheric temperature at Earth's surface level measured in degrees Celcius and derived from the meteorological data files.	Rel 34 GLAS Binary Data	DS_UTCTime_1

Group: /Data_40HZ/

This group contains data with a rate of 40HZ. 40Hz data may be indexed to the 1HZ data using the i_rec_ndx parameter in each respective time group.

Dimension Scales

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
DS_UTCTime_40	DOUBLE (UNLIMITED)	Transmit time of each shot in J2000 seconds (time)	seconds since 2000-01-01 12:00:00 UTC	The transmit time of each shot in the 1 second frame measured as UTC seconds elapsed since Jan 1 2000 12:00:00 UTC. This time has been derived from the GPS time accounting for leap seconds.	Rel 34 GLAS Binary Data	NOT_SET				
DS_DEMhiresArElv	INTEGER (UNLIMITED)	Location index for D_DEMhiresArElv (NOT_SET)	NOT_SET	This array indicates the relative position of each d_DEMhiresArElv measurement. Direction is relative to the spot and indicated in cardinal points. The position of the spot is indicated as ORIGIN. <table border="1" data-bbox="824 1226 1245 1390"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>1, 2, 3, 4, 5, 6, 7, 8, 9</td> <td>NW N NE W ORIGIN E SW S SE</td> </tr> </tbody> </table>	flag values	flag_meanings	1, 2, 3, 4, 5, 6, 7, 8, 9	NW N NE W ORIGIN E SW S SE	Constants	NOT_SET
flag values	flag_meanings									
1, 2, 3, 4, 5, 6, 7, 8, 9	NW N NE W ORIGIN E SW S SE									
DS_PeakNumber	INTEGER (UNLIMITED)	Peak index number (NOT_SET)	NOT_SET	This array indicates the index of the detected waveform peak for several parameters. PeakNumber=1 indicates the detected peak closest to the ground; PeakNumber=6 indicates the peak furthest from the ground.	Constants	NOT_SET				

Group: Data_40HZ/Time

This group contains the 40HZ index and time-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_UTCTime_40	DOUBLE (UNLIMITED)	GLAS shot UTC time	seconds since 2000-01-01 12:00:00 UTC	Transmit time of each shot in the 1 second frame measured as UTC seconds elapsed since Jan 1 2000 12:00:00 UTC. This time has been derived from the GPS time accounting for leap seconds.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
i_rec_ndx	INTEGER (UNLIMITED)	GLAS Record Index (NOT_SET)	NOT_SET	Unique index that relates this record to the corresponding record(s) in each GLAS data product.	Rel 34 GLAS Binary Data	DS_UTCTime_40
i_shot_count	INTEGER (UNLIMITED)	GLAS shot counter (NOT_SET)	NOT_SET	Identifies each laser shot within a record index. A combination of i_rec_ndx and i_shot_count can be used to uniquely identify each GLAS laser shot.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Geolocation

This group contains geolocation-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_lat	DOUBLE (UNLIMITED)	Coordinate Data, Latitude, specific to ice sheet range (NOT_SET)	degrees_north	The geodetic latitude of the laser spot computed from the Precision orbit, precision attitude, and ice-sheet specific range after instrument corrections, atmospheric delays and tides have been applied. The values are in degrees north.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_lon	DOUBLE (UNLIMITED)	Coordinate Data, Longitude, specific to ice sheet range (NOT_SET)	degrees_east	The longitude of the laser spot computed from the Precision orbit, precision attitude, and ice-sheet specific range after instrument corrections, atmospheric delays and tides have been applied. The values are in degrees east.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Elevation_Surfaces

This group contains the surface-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_elev	DOUBLE (UNLIMITED)	Land surface Elevation (height_above_reference_ellipsoid)	meters	Surface elevation with respect to the ellipsoid at the spot location determined by the land specific range after instrument corrections, atmospheric delays and tides have been applied. The saturation elevation correction (d_satElevCorr) has not been applied and needs to be added to this elevation. This can be over a one meter correction. If it is invalid then the elevation should not be used. The saturation correction flag (sat_corr_flg) is an important flag to understand the possible quality of the elevation data. The saturation index (i_satNdx) can be used for more understanding of concerns on data quality from saturation effects. Also no correction for pulse spreading from forward scatter has been applied.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_LandVar	DOUBLE (UNLIMITED)	Standard Deviation of the land Gaussian Fit (NOT_SET)	volts	The Standard deviation of the difference between the functional fit and the received echo using alternate parameters. It is directly taken from GLA05 parameter d_wFFitSDev_1 (Alternate).	Rel 34 GLAS Binary Data	DS_UTCTime_40

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_refRng	DOUBLE (UNLIMITED)	Reference Range (altimeter_range)	meters	Range in distance calculated from the time between the centroid of the transmit pulse and the farthest gate from the spacecraft of the received pulse. See the rngcorrflg to determine any corrections that have been applied.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Elevation_Corrections

This group contains elevation-related corrections.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_dTrop	DOUBLE (UNLIMITED)	Range Correction, Dry Troposphere (altimeter_range_correction_due_to_dry_troposphere)	meters	The range correction due to the dry troposphere. Validity is based on results of finding a range with the standard fit.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_wTrop	DOUBLE (UNLIMITED)	Range Correction_Wet Troposphere (altimeter_range_correction_due_to_wet_troposphere)	meters	The range correction due to the wet troposphere. (See ATBDs)	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_satElevCorr	DOUBLE (UNLIMITED)	Saturation Elevation Correction (NOT_SET)	meters	Correction to elevation for saturated waveforms. This correction has NOT been applied to the data. To apply it, SUBTRACT the correction from the range estimate. To apply the correction to the elevations it must be ADDED to the elevation estimates. See also: Saturation Correction Guidance .	Rel 34 GLAS Binary Data	DS_UTCTime_40

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_ElevBiasCorr	DOUBLE (UNLIMITED)	Elevation Bias Correction (NOT_SET)	meters	Correction to elevation based on post flight analysis for biases determined for each campaign. This bias correction has not been applied to the data. To apply it SUBTRACT, the correction from the range estimate. To apply the correction to the elevations it must be ADDED to the elevation estimates.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_GmC	DOUBLE (UNLIMITED)	Range correction in m calc from Trans pulse peak loc to centroid (NOT_SET)	m	The difference of the Gaussian fit to the transmit pulse and the centroid of it. This correction was applied to the range before the computation of elevation. It is an additive correction to an elevation relative to Tx centroid to make the elevation relative to the Tx Gaussian.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Elevation_Angles

This group contains pointing angle parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_beamAzimuth	DOUBLE (UNLIMITED)	Azimuth (NOT_SET)	degrees	The direction, eastwards from north, of the laser beam vector as seen by an observer at the laser ground spot viewing toward the spacecraft (i.e., the vector from the ground to the spacecraft). When the spacecraft is precisely at the geodetic zenith, the value will be 99999 degrees.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_beamCoelv	DOUBLE (UNLIMITED)	Co-elevation (NOT_SET)	degrees	Co-elevation (CE) is direction from vertical of the laser beam as seen by an observer located at the laser ground spot.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Elevation_Offsets

The group contains elevation offsets. These offsets allow the elevation for the specific surface types to be derived.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_gpCntRngOff	DOUBLE (UNLIMITED, 6)	Centroid Range Increment for all 6 peaks (NOT_SET)	meters	i_gpCntRngOff (Centroid Range Increment for Gaussian Fits) is a 6-element array that contains offsets from the reference range to the the peak locations of the receive waveform alternate Gaussian fits. There are at least one and at most six fits, which can be overlapping. The first offset in the array corresponds to the location of the fit with the lowest elevation (furthest from the spacecraft), and the last to the highest.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_isRngOff	DOUBLE (UNLIMITED)	Ice Sheet Range Offset (NOT_SET)	meters	Range offset to be added to d_refRng to calculate the range using the algorithm deemed appropriate for ice sheets.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_ldRngOff	DOUBLE (UNLIMITED)	Land Range Offset (NOT_SET)	meters	Range offset to be added to d_refRng to calculate the range using the algorithm deemed appropriate for land.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_sigBegOff	DOUBLE (UNLIMITED)	Signal Begin Range Increment (NOT_SET)	meters	Offset to be added to d_refRng to give the range in distance to the location of the received echo calculated at the beginning of signal (closest to the spacecraft) using alternate parameters.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_sigEndOff	DOUBLE (UNLIMITED)	Signal End Range Increment (NOT_SET)	meters	Offset to be added to d_refRng to give the range in distance to the location of the received echo calculated at the end of signal (farthest from the spacecraft) using alternate parameters.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Quality

This group contains quality-related parameters and flags.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
rng_uqf_sigbeg1_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Signal begin range increment flag (standard). <table border="1" data-bbox="857 1436 1214 1575"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_sigend1_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Signal end range increment flag (standard). <table border="1" data-bbox="857 1696 1214 1835"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
rng_uqf_thres1_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Threshold retracker range increment flag (standard). <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_cent1_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Centroid retracker range increment flag (standard). <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_sigbeg2_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Signal begin range increment flag (alternate). <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_sigend2_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Signal end range increment flag (alternate). <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_thres2_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Threshold retracker range increment flag (alternate). <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_cent2_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Centroid retracker range increment flag (alternate). <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_is_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Ice sheet range increment flag. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
rng_uqf_si_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Sea ice range increment flag. <table border="1" data-bbox="857 247 1214 384"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_ld_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Land range increment flag. <table border="1" data-bbox="857 478 1214 615"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
rng_uqf_oc_flg	INTEGER_1 (UNLIMITED)	Range Offset Quality/Use Flag (NOT_SET)	NOT_SET	Ocean range increment flag. <table border="1" data-bbox="857 709 1214 846"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									
sat_corr_flg	INTEGER_1 (UNLIMITED)	Saturation Correction Flag (NOT_SET)	NOT_SET	Saturation Correction Flag; Indicates if the saturation is Not Saturated ($i_satNdx < 2$) or No Signal; Inconsequential ($i_satNdx \geq 2$ & $i_pctSat < 2.0$); is Applicable ($i_satNdx \geq 2$ & $i_pctSat \geq 2.0$ & Full Width* < 100ns); is Not Computable; is Not Applicable ($i_satNdx \geq 2$ & $i_pctSat \geq 2.0$ & Full Width* >= 100ns). <table border="1" data-bbox="857 1171 1226 1444"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2, 3, 4</td> <td>not_saturated; inconsequential; applicable; not_computed; not_applicable</td> </tr> </table> Note: the file-level metadata erroneously indicates that six values are used: 0, 1, 2, 3, 4, 5. As described above, only five values are defined. See also: Saturation Correction Guidance	flag values	flag_meanings	0, 1, 2, 3, 4	not_saturated; inconsequential; applicable; not_computed; not_applicable	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1, 2, 3, 4	not_saturated; inconsequential; applicable; not_computed; not_applicable									
elev_use_flg	INTEGER_1 (UNLIMITED)	Elevation use flag (NOT_SET)	NOT_SET	Flag indicating whether the elevations on this record should be used. <table border="1" data-bbox="857 1770 1214 1906"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>valid not_valid</td> </tr> </table>	flag values	flag_meanings	0, 1	valid not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	valid not_valid									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
att_pad_use_flg	INTEGER_1 (UNLIMITED)	Pad Use Flag (NOT_SET)	NOT_SET	PAD Use Flag; Indicates if PAD used to determine spot location. <table border="1" data-bbox="857 275 1190 411"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>used not_used</td> </tr> </table>	flag values	flag_meanings	0, 1	used not_used	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	used not_used									
att_calc_pad_flg	INTEGER_1 (UNLIMITED)	Calc Pad Use Flag (NOT_SET)	NOT_SET	Calc PAD Use Flag; Indicates if new PAD or pass-thru PAD was used to determine orbit. <table border="1" data-bbox="857 562 1190 699"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>new pass_thru</td> </tr> </table>	flag values	flag_meanings	0, 1	new pass_thru	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	new pass_thru									
att_lpa_flg	INTEGER_1 (UNLIMITED)	LPA Problem Flag (NOT_SET)	NOT_SET	LPA Problem Flag; Indicates if LPA is good, missing or noisy. <table border="1" data-bbox="857 825 1226 1014"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1, 2</td> <td>good missing noisy</td> </tr> </table>	flag values	flag_meanings	0, 1, 2	good missing noisy	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1, 2	good missing noisy									
sigma_att_flg	INTEGER_1 (UNLIMITED)	Attitude Quality Indicator (NOT_SET)	NOT_SET	Attitude quality indicator flag. <table border="1" data-bbox="857 1115 1226 1304"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 50, 100, 127</td> <td>good warning bad not_valid</td> </tr> </table>	flag values	flag_meanings	0, 50, 100, 127	good warning bad not_valid	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 50, 100, 127	good warning bad not_valid									
i_satNdx	INTEGER (UNLIMITED)	Saturation Index (NOT_SET)	ns	The count of the number of gates in a waveform which have an amplitude greater than or equal to i_satNdxTh (set in anc07_0004). The value 126 means 126 or more gates are above the saturation index threshold (i_satNdxth).	Rel 34 GLAS Binary Data	DS_UTCTime_40				

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_pctSAT	DOUBLE (UNLIMITED)	Percent Saturation (NOT_SET)	percent	Percent saturation (d_pctSAT) is calculated using the formula: $d_pctSAT = 100 * (\text{saturation index}) / (\text{signal end} - \text{signal begin in nanoseconds})$. The alternate signal end/begin are used for GLA14 d_pctSAT, while the standard fit values are used for GLA06, 12, 13, and 15. The Saturation elevation correction is not applied in the geolocation processing computation of lat, lon and elev. Because the saturation corrections are small and data is acquired within 5 deg off nadir, effects on lat and lon can be ignored. To apply the saturation elevation correction to the elevations on the products it must be ADDED to the elevation estimates. Reported elevations for returns with invalid d_satElevCorr values and sat_corr_flg values of 3 or 4 are likely to have large, uncorrectable errors and should be excluded from analyses. See also: Saturation Correction Guidance .	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Elevation_Flags

This group contains flags related to the elevation estimates for each shot.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
elv_cnt_1_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Standard parameterization; true if centroid of received pulse between signal begin and signal end defined for standard parameterization used to calculate elevation. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									
elv_cnt_2_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Alternate parameterization; indicates if centroid of received pulse between signal begin and signal end defined for alternate parameterization used to calculate elevation. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									
elv_peak_1_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Standard parameterization; Indicates if location of last Gaussian peak in received pulse for standard parameterization used to calculate elevation. <table border="1"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
e1v_peak_2_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Alternate parameterization; Indicates if location of last Gaussian peak in received pulse for alternate parameterization used to calculate elevation. <table border="1" data-bbox="800 302 1105 441"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									
e1v_thres_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Threshold retracker; Indicates if location of threshold retracker used to calculate elevation. <table border="1" data-bbox="800 564 1105 703"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									
e1v_gauss_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Gaussian; Indicates if location associated with gaussian with largest peak used to calculate elevation. <table border="1" data-bbox="800 852 1105 991"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									
e1v_other_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Other algorithm; Indicates if other algorithm used to calculate elevation - see software release documentation for details. <table border="1" data-bbox="800 1140 1105 1278"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									
e1v_cloud_flg	INTEGER_1 (UNLIMITED)	Elevation Definition Flag (NOT_SET)	NOT_SET	Cloud contamination; Indicates if Gain > flag value, indicating probable cloud contamination. <table border="1" data-bbox="800 1402 1105 1541"> <tr> <td>flag values</td> <td>flag_meanings</td> </tr> <tr> <td>0, 1</td> <td>false true</td> </tr> </table>	flag values	flag_meanings	0, 1	false true	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1	false true									

Group: Data_40HZ/Transmit_Energy

This group contains transmit energy parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_TxNrg	DOUBLE (UNLIMITED)	1064 nm Laser Transmit Energy (NOT_SET)	joules	The 1064 nm laser pulse transmitted energy in energy units, computed from the digitized outgoing pulse, and the transmit gain.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Geophysical

This group contains geophysical parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description
d_d2refTrk	DOUBLE (UNLIMITED)	Distance to the reference ground track (NOT_SET)	meters	Distance to the reference ground track.
d_DEM_elv	DOUBLE (UNLIMITED)	DEM Elevation (NOT_SET)	meters	Elevation at the footprint location from the SRTM30 (GTOPO30 + SRTM) Digital Elevation Model (DEM). The reference frame for the DEM elevation was changed to the TOPEX/Poseidon ellipsoid to make it consistent with the GLAS elevations.
d_DEMhiresArElv	DOUBLE (UNLIMITED, 9)	DEMhiresArElv (NOT_SET)	meters	d_DEMhiresArElv is a 9 element array of high resolution DEM values. The array index corresponds to the position of the DEM value relative to the spot. (5) is the footprint center.
d_eqElv	DOUBLE (UNLIMITED)	Equilibrium Tide Elevation (sea_surface_height_amplitude_due_to_equilibrium_ocean_tide)	meters	The equilibrium (long period) tide at last valid shot over the ocean.
d_erElv	DOUBLE (UNLIMITED)	Solid Earth Tide Elevation (NOT_SET)	meters	The solid earth tide elevation.
d_gdHt	DOUBLE (UNLIMITED)	Geoid (geoid_height_above_reference_ellipsoid)	meters	The height of the geoid above the ellipsoid. EGM2008 geoid height above the reference ellipsoid.
d_ldElv	DOUBLE (UNLIMITED)	Load Tide Elevation (NOT_SET)	meters	The load tide elevation applied to each shot.
d_ocElv	DOUBLE (UNLIMITED)	Ocean Tide Elevation (sea_surface_height_amplitude_due_to_non_equilibrium_ocean_tide)	meters	The ocean tide elevation from the TPX07.1 tide model.
d_deltaEllip	DOUBLE (UNLIMITED)	Delta Ellipsoid (NOT_SET)	meters	Surface elevation (T/P ellipsoid) minus surface elevation (WGS84 ellipsoid).

Label	Datatype (Dimensions)	long_name (standard_name)	units	description				
d_poTide	DOUBLE (UNLIMITED)	Pole Tide (sea_surface_height_amplitude_due_to_pole_tide)	meters	Pole tide: an ocean tide which is the result of the Chandler wobble (a free nutation of the Earth caused by fluctuating pressure on the bottom of the ocean, caused by temperature and salinity changes and wind-driven changes in the circulation of the oceans).				
i_DEM_hires_src_1	INTEGER_1 (UNLIMITED)	High Resolution Source Flag (NOT_SET)	NOT_SET	High resolution DEM source provider; Indicates if no high res source available, unfinished research Shuttle Radar Topography Mission (SRTM) C-band 90m DEM produced by JPL (+-1.1km E-W swath), finished' SRTM C-band 90 m DEM produced by NGA (+-2.1km E-W swath), ICESat Greenland V1 1km DEM, ICESat Antarctica V1 500m DEM, 90m Canadian Digital Elevation Data (CDED), Data in overlap area of SRTM and CDED. Value reported is from finished SRTM C-band 90 m DEM. <table border="1" data-bbox="1281 1010 1549 1314"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3, 4, 5, 6</td> <td>none pre_srtm srtm greenland antarctica cded_90 olap_srtm</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3, 4, 5, 6	none pre_srtm srtm greenland antarctica cded_90 olap_srtm
flag values	flag_meanings							
0, 1, 2, 3, 4, 5, 6	none pre_srtm srtm greenland antarctica cded_90 olap_srtm							

Group: Data_40HZ/Reflectivity

This group contains reflectivity parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_reflctUC	DOUBLE (UNLIMITED)	reflctUC (NOT_SET)	NOT_SET	Reflectivity, not corrected for atmospheric effects, is calculated as $Refl = R/T$, where R is the received energy after it has been scaled for range, and T is the transmitted energy. i_reflctUC has also been calibrated for gain non-linearity (only for non-saturated waveforms), ground truth calibration and boresight shift shadowing (BSS). It is not corrected for saturation effects. If the shot is saturated (satindex above 2) then to correct for saturation the reflectivity estimate needs to be multiplied by the ratio of the corrected energy to the uncorrected energy (sat corrected reflectivity = $d_reflctUC * (d_RecNrgAll + d_satNrgCorr)/d_RecNrgAll$). The atmospheric corrected reflectivity may be calculated from this uncorrected reflectivity by multiplying it by $d_reflCor_atm$. d_reflctUC is invalid where d_satNrgCorr is invalid.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_sDevNsOb1	DOUBLE (UNLIMITED)	Standard deviation of 1064 nm Background noise, (alternate) (NOT_SET)	volts	The standard deviation of the background noise (alternate parameters).	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_satNrgCorr	DOUBLE (UNLIMITED)	Saturation Energy Correction (NOT_SET)	Joules	Correction to energy for saturated waveforms. This correction has not been applied to the energy. It should be ADDED to any echo pulse energy calculated from the pulse area under the waveform. Also any reflectivity estimates need to be corrected for this error in energy measurement. See also: Saturation Correction Guidance .	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_RecNrgAll	DOUBLE (UNLIMITED)	Received Energy signal begin to signal end (NOT_SET)	Joules	This is calculated by taking the area under the received waveform (referenced to the observed noise) from all responses between the noise crossing before the first threshold crossing and the noise crossing after the last threshold crossing. It is a rescaled value from the GLA01 parameter d_recNrgAll_EU and is not recomputed.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Waveform

This group contains waveform-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_skew1	DOUBLE (UNLIMITED)	Skewness of Received Echo (alternate) (NOT_SET)	NOT_SET	Skewness of the received echo from signal begin to signal end using alternate parameters.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_kurt1	DOUBLE (UNLIMITED)	Kurtosis of Received Echo (alternate) (NOT_SET)	NOT_SET	Kurtosis of the received echo from signal begin to signal end using alternate parameters.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_maxRecAmp	DOUBLE (UNLIMITED)	Max Amplitude of Received Echo (NOT_SET)	volts	Maximum amplitude of the received echo.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_maxSmAmp	DOUBLE (UNLIMITED)	Peak Amplitude of Smoothed Received Echo (NOT_SET)	volts	The peak amplitude of the received echo after it has been smoothed to remove high frequency noise (see ATBD).	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_Gamp	DOUBLE (UNLIMITED, 6)	Amplitudes of Gaussians (NOT_SET)	volts	Amplitude of each gaussian solved for (up to six), using the alternate parameters. See <i>i_numPk</i>	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_Garea	DOUBLE (UNLIMITED, 6)	Area under Gaussian (NOT_SET)	volts * ns	Area under each of the gaussians solved for (up to six), using alternate parameters. See <i>i_numPk</i>	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_Gsigma	DOUBLE (UNLIMITED, 6)	Sigma of Gaussians (NOT_SET)	ns	Width (sigma) of each gaussian solved for (up to six), using alternate parameters. See <i>i_numPk</i>	Rel 34 GLAS Binary Data	DS_UTCTime_40
i_nPeaks1	INTEGER (UNLIMITED)	Initial Number of Peaks in received echo (alternate) (NOT_SET)	count	The initial number of peaks of the received echo; determined from the smoothed waveform, using alternate parameters.	Rel 34 GLAS Binary Data	DS_UTCTime_40
i_numPk	INTEGER (UNLIMITED)	Number of Peaks found in the Return (NOT_SET)	count	The number of peaks in the waveform produced by the gaussian filtering, using alternate parameters.	Rel 34 GLAS Binary Data	DS_UTCTime_40
i_gval_rcv	INTEGER (UNLIMITED)	Gain Value used for Received Pulse (NOT_SET)	counts	Gain value used for received pulse - uncalibrated.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Group: Data_40HZ/Atmosphere

This group contains atmosphere-related parameters.

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates
d_FRir_cldtop	DOUBLE (UNLIMITED)	Full Resolution 1064 Cloud Top (NOT_SET)	meters	Full resolution (40 Hz) cloud top height obtained from the 1064 atmospheric channel. This parameter is in GLA09.	Rel 34 GLAS Binary Data	DS_UTCTime_40
d_FRir_intsig	DOUBLE (UNLIMITED)	Full Resolution 1064 Integrated Signal (NOT_SET)	1/(m-sr)	Though called 'integrated signal' this is actually an average of all bins in the above-ground portion of the 1064 40 Hz profile with values above the threshold of 1.0e-7 (1/(m-sr) units). This parameter is extracted from the equivalent parameter on GLA09.	Rel 34 GLAS Binary Data	DS_UTCTime_40

Label	Datatype (Dimensions)	long_name (standard_name)	units	description	source	coordinates				
FRir_qa_flg	INTEGER_1 (UNLIMITED)	Full Resolution 1064 Quality Flag (NOT_SET)	NOT_SET	<p>Full resolution 1064 Quality Flag; 0 - 12 indicate Cloud detected by cloud search algorithm with higher numbers indicating a stronger average signal from the region starting at cloud top and extending 500 m below cloud top height; 13 = Indicates the possible presence of a cloud based on the value of the integrated signal parameter (i_FRir_intsig) that was not detected directly by the cloud search algorithm. When this occurs, the 40 Hz cloud top height (i_FRir_cldtop) is set to a value of 10.0 km; 14 = Indicates the likely presence of low clouds (< 150 m) based on elevated signal from the two bins above the ground return bin that were not detected directly by the cloud search algorithm. When this occurs, the 40 Hz cloud top height (i_FRir_cldtop) is set to a value of 0.10; 15 = No clouds.</p> <table border="1"> <thead> <tr> <th>flag values</th> <th>flag_meanings</th> </tr> </thead> <tbody> <tr> <td>0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15</td> <td>0 1 2 3 4 5 6 7 8 9 10 11 12 possible likely</td> </tr> </tbody> </table>	flag values	flag_meanings	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15	0 1 2 3 4 5 6 7 8 9 10 11 12 possible likely	Rel 34 GLAS Binary Data	DS_UTCTime_40
flag values	flag_meanings									
0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15	0 1 2 3 4 5 6 7 8 9 10 11 12 possible likely									

/ANCILLARY_DATA

/ANCILLARY_DATA

Attribute	Example Value
Campaign	2A
glas_osc_rate	1.000000023
glas_osc_rate_date	2003-10-30
glas_osc_rate_time	00:00:00
sc_osc_rate	0.99999998854809
sc_osc_rate_date	2003-10-30
sc_osc_rate_time	00:00:00
internal_time_delay	0.0000151100
internal_time_delay_date	2003-10-30
internal_time_delay_time	00:00:00
internal_range_delay	9.5560
internal_range_delay_date	2003-10-30
internal_range_delay_time	00:00:00

Attribute	Example Value
Additional_Attribute	SP_ICE_PATH_NO, SP_ICE_GLAS_StartBlock, SP_ICE_GLAS_EndBlock, ReferenceOrbit, Track, Timing_Drift, PercentGroundHit, Cycle, OrbitQuality, Instance, Range_Bias, Range_Bias_Date, Range_Bias_Time, Timing_Bias, Timing_Bias_Date, Timing_Bias_Time
globAvSrfPres1	100964.3794153
gASP_t1	122385600.0000000
globAvSrfPres2	100965.0504048
gASP_t2	122407200.0000000
globAvSrfPres3	100971.5330532
gASP_t3	122428800.0000000
globAvSrfPres4	100976.6362863
gASP_t4	122450400.0000000
globAvSrfPres5	100979.7656113
gASP_t5	122472000.0000000
internal_range_delay_desc	Internal range calibration bias determined during GLAS instrument integration testing and validated in-flight, meters.
internal_time_delay_desc	Internal time calibration bias determined during GLAS instrument integration testing and validated in-flight, seconds.

/METADATA

/METADATA

Attribute	Example Value
description	This group contains structured, computer-parseable ECHO-style collection and inventory-level metadata.
HDFVersion	HDF5 1.8.9
ControlFile	cf_name=CTL00_000_20140818_2598059_01_gla14_h5_convert.ct1

/METADATA/COLLECTIONMETADATA

Attribute	Example Value
DLLName	libDsESDTG1GLASPoly.001Sh.so
GranuleTimeDuration	81280
SpatialSearchType	Orbit
DataFileFormat	HDF5
ScienceMimeType	application/x-hdfeos

Attribute	Example Value
BrowseMimeType	application/x-hdfeos
BrowseOnlineMimeType	image/jpeg
ShortName	GLAH14
LongName	GLAS/ICESat L2 Global Land Surface Altimetry Data (HDF5)
CollectionDescription	GLAH14 contains the land elevation and elevation distribution corrected for geodetic and atmospheric affects calculated from algorithms fine-tuned for over land returns. Data granules contain 14 orbits of data within the land mask.
VersionID	34
CitationforExternalPublication	The data used in this study were produced by the GLAS Science Team at the ICESat Science Investigator-led Processing System (I-SIPS) at NASA/GSFC. The data archive site is the NSIDC DAAC.
CollectionState	In Work
MaintenanceandUpdateFrequency	Daily
AccessConstraints	Data may not be reproduced or distributed without including the CitationForExternalPublication for this product included in this Metadata. Data may not be distributed in an altered form without the written permission of the GLAS Science Team.
TemporalKeyword	Day
SpatialKeyword	Global

/METADATA/COLLECTIONMETADATA/AdditionalAttributes

Attribute	Example Value
PercentGroundHit	AdditionalAttributesContainer
OrbitQuality	AdditionalAttributesContainer
Track	AdditionalAttributesContainer
Instrument_State	AdditionalAttributesContainer
Timing_Bias	AdditionalAttributesContainer
Timing_Drift	AdditionalAttributesContainer
ReferenceOrbit	AdditionalAttributesContainer
SP_ICE_PATH_NO	AdditionalAttributesContainer
SP_ICE_GLAS_StartBlock	AdditionalAttributesContainer
SP_ICE_GLAS_EndBlock	AdditionalAttributesContainer
Cycle	AdditionalAttributesContainer
Instance	AdditionalAttributesContainer

Attribute	Example Value
Range_Bias	AdditionalAttributesContainer
Instrument_State_Date	AdditionalAttributesContainer
Instrument_State_Time	AdditionalAttributesContainer
Range_Bias_Date	AdditionalAttributesContainer
Range_Bias_Time	AdditionalAttributesContainer
Timing_Bias_Date	AdditionalAttributesContainer
Timing_Bias_Time	AdditionalAttributesContainer
Timing_Drift_Date	AdditionalAttributesContainer
Timing_Drift_Time	AdditionalAttributesContainer
identifier_product_doi	AdditionalAttributesContainer
identifier_file_uuid	AdditionalAttributesContainer
identifier_product_doi_authority	AdditionalAttributesContainer

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Cycle

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	A count of the number of exact repeats of this reference orbit.
AdditionalAttributeName	Cycle
ParameterUnitsofMeasurement	counts
ParameterRangeBegin	0
ParameterRangeEnd	250

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Instance

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	The number of times that we have returned to a specific reference orbit.
AdditionalAttributeName	Instance
ParameterUnitsofMeasurement	counts
ParameterRangeBegin	1
ParameterRangeEnd	99

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Instrument_State

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	Flag word that indicates which redundant units (laser, detector, oscillator) of the GLAS instrument are in operation.
AdditionalAttributeName	Instrument_State
ParameterUnitsofMeasurement	Flag word
ParameterRangeBegin	0
ParameterRangeEnd	5

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Instrument_State_Date

Attribute	Example Value
AdditionalAttributeDatatype	date
AdditionalAttributeDescription	The date that corresponds to the first valid Instrument_State. There are a maximum of two per granule.
AdditionalAttributeName	Instrument_State_Date

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Instrument_State_Time

Attribute	Example Value
AdditionalAttributeDatatype	time
AdditionalAttributeDescription	The time that corresponds to the first valid Instrument_State. There are a maximum of two per granule.
AdditionalAttributeName	Instrument_State_Time

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/OrbitQuality

Attribute	Example Value
AdditionalAttributeDatatype	varchar
AdditionalAttributeDescription	Status word that states what type of orbit was used during processing of the data for the granule. It specifies the models used in the orbit determination program. This provides an indication of the quality of the orbits being applied to the data.
AdditionalAttributeName	OrbitQuality
ParameterUnitsofMeasurement	Flag

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/PercentGroundHit

Attribute	Example Value
AdditionalAttributeDatatype	float

Attribute	Example Value
AdditionalAttributeDescription	Percent of data for this granule that had a detected ground return of the transmitted laser pulse.
AdditionalAttributeName	PercentGroundHit
ParameterUnitsofMeasurement	Percent
ParameterRangeBegin	0.0
ParameterRangeEnd	100.0
ParameterValueAccuracy	1
ParameterMeasurementResolution	1

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Range_Bias

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	The additive calibration correction in millimeters to apply to range based on the science team cal/val activities.
AdditionalAttributeName	Range_Bias
ParameterUnitsofMeasurement	Millimeters
ParameterRangeBegin	-10000
ParameterRangeEnd	10000
ParameterValueAccuracy	1
ParameterMeasurementResolution	1

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Range_Bias_Date

Attribute	Example Value
AdditionalAttributeDatatype	date
AdditionalAttributeDescription	The date that corresponds to the first valid Range_Bias. There are a maximum of two per granule.
AdditionalAttributeName	Range_Bias_Date

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Range_Bias_Time

Attribute	Example Value
AdditionalAttributeDatatype	time
AdditionalAttributeDescription	The time that corresponds to the first valid Range_Bias. There are a maximum of two per granule.
AdditionalAttributeName	Range_Bias_Time

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/ReferenceOrbit

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	Assigned number for which exact orbital elements describe the exact repeat orbit pattern.
AdditionalAttributeName	ReferenceOrbit
ParameterUnitsofMeasurement	Assigned number
ParameterRangeBegin	1
ParameterRangeEnd	30000

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/SP_ICE_GLAS_EndBlock

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	Integer number within GLAS coverage scheme in which granule data ends.
AdditionalAttributeName	SP_ICE_GLAS_EndBlock
ParameterRangeBegin	1
ParameterRangeEnd	360

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/SP_ICE_GLAS_StartBlock

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	Integer number within GLAS coverage scheme in which granule data starts.
AdditionalAttributeName	SP_ICE_GLAS_StartBlock
ParameterRangeBegin	1
ParameterRangeEnd	360

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/SP_ICE_PATH_NO

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	Number which represents the GLAS path number.
AdditionalAttributeName	SP_ICE_PATH_NO
ParameterRangeBegin	1
ParameterRangeEnd	32768

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Timing_Bias

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	The time tag error determined by the calibration team that was added to the time tags to compute the true time of data as provided on the granule.
AdditionalAttributeName	Timing_Bias
ParameterUnitsofMeasurement	Microseconds
ParameterRangeBegin	-1000000
ParameterRangeEnd	+1000000

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Timing_Bias_Date

Attribute	Example Value
AdditionalAttributeDatatype	date
AdditionalAttributeDescription	The date that corresponds to the first valid Timing_Bias. There are a maximum of two per granule.
AdditionalAttributeName	Timing_Bias_Date

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Timing_Bias_Time

Attribute	Example Value
AdditionalAttributeDatatype	time
AdditionalAttributeDescription	The time that corresponds to the first valid Timing_Bias. There are a maximum of two per granule.
AdditionalAttributeName	Timing_Bias_Time

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Timing_Drift

Attribute	Example Value
AdditionalAttributeDatatype	float
AdditionalAttributeDescription	This is the ratio of the true time for a one second oscillator tick to nominal one
AdditionalAttributeName	Timing_Drift
ParameterRangeBegin	-1.0
ParameterRangeEnd	+1.0

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Timing_Drift_Date

Attribute	Example Value
AdditionalAttributeDatatype	date

Attribute	Example Value
AdditionalAttributeDescription	The date that corresponds to the first valid <code>Timing_Drift</code> . There are a maximum of two per granule.
AdditionalAttributeName	<code>Timing_Drift_Date</code>

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Timing_Drift_Time

Attribute	Example Value
AdditionalAttributeDatatype	time
AdditionalAttributeDescription	The time that corresponds to the first valid <code>Timing_Drift</code> . There are a maximum of two per granule.
AdditionalAttributeName	<code>Timing_Drift_Time</code>

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/Track

Attribute	Example Value
AdditionalAttributeDatatype	int
AdditionalAttributeDescription	The unique number assigned for each repeat ground track (one orbit) of the reference orbit.
AdditionalAttributeName	Track
ParameterUnitsofMeasurement	counts
ParameterRangeBegin	0
ParameterRangeEnd	3000

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/identifier_file_uuid

Attribute	Example Value
AdditionalAttributeDatatype	varchar
AdditionalAttributeDescription	Universally unique identifier for this data product's files
AdditionalAttributeName	<code>identifier_file_uuid</code>

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/identifier_product_doi

Attribute	Example Value
AdditionalAttributeDatatype	varchar
AdditionalAttributeDescription	Digital object identifier that uniquely identifies this data product
AdditionalAttributeName	<code>identifier_product_doi</code>

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/identifier_product_doi/InformationContent

Attribute	Example Value
-----------	---------------

Attribute	Example Value
ParameterValue	10.5067/ICESAT/GLAS/DATA211

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/identifier_product_doi_authority

Attribute	Example Value
AdditionalAttributeDatatype	varchar
AdditionalAttributeDescription	URL of the digital object identifier resolving authority
AdditionalAttributeName	identifier_product_doi_authority

/METADATA/COLLECTIONMETADATA/AdditionalAttributes/identifier_product_doi_authority/InformationContent

Attribute	Example Value
ParameterValue	http://dx.doi.org/10.5067/ICESAT/GLAS/DATA211

/METADATA/COLLECTIONMETADATA/CSDTDescription

Attribute	Example Value
PrimaryCSDT	n-Dim Array of Records
IndirectReference	tracks/orbits
Implementation	HDF
CSDTComments	Two dimensional arrays with six segments per track (orbit).The segments are: (1)equator to +50 lat,(2)+50 lat across pole to +50 lat,(3)+50 deg lat to equator,(4)equator to -50 lat,(5)-50 deg lat across pole to -50 deg lat,(6)-50 deg lat to equator.

/METADATA/COLLECTIONMETADATA/CollectionAssociation

Attribute	Example Value
GLAH06	CollectionAssociationContainer
GLAH05	CollectionAssociationContainer
GLAH01	CollectionAssociationContainer
GLA00	CollectionAssociationContainer
GLAH12	CollectionAssociationContainer
GLAH13	CollectionAssociationContainer
GLAH15	CollectionAssociationContainer

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLA00

Attribute	Example Value
CollectionType	Science Associated

Attribute	Example Value
CollectionUse	The initial collection of GLAS instrument data downlinked from the spacecraft
ShortName	GLA00
VersionID	1

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLAH01

Attribute	Example Value
CollectionType	Science Associated
CollectionUse	Level 1A file containing altimeter height, waveform data, and other data required to produce the Level 1B waveform products
ShortName	GLAH01
VersionID	33

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLAH05

Attribute	Example Value
CollectionType	Input
CollectionUse	Level 1B file containing: the range corrections to the range from the waveform retracking algorithms, the surface roughness estimate, and the reflectance
ShortName	GLAH05
VersionID	34

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLAH06

Attribute	Example Value
CollectionType	Input
CollectionUse	Level 1B file containing elevations, elevation corrections, surface roughness, reflectance, and associated timing and data quality information
ShortName	GLAH06
VersionID	34

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLAH12

Attribute	Example Value
CollectionType	Science Associated
CollectionUse	Level 2 file containing: corrected ice sheet elevations above the reference ellipsoid, surface roughness, reflectance, and the corrections that were used. The product parameters are the result of product-specialized waveform fitting.
ShortName	GLAH12

Attribute	Example Value
VersionID	34

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLAH13

Attribute	Example Value
CollectionType	Science Associated
CollectionUse	Level 2 file containing: Sea Ice Elevation, Reflectance, and Roughness, Ice Berg Elevations and Roughness. The product parameters are the result of product-specialized waveform fitting.
ShortName	GLAH13
VersionID	34

/METADATA/COLLECTIONMETADATA/CollectionAssociation/GLAH15

Attribute	Example Value
CollectionType	Science Associated
CollectionUse	Level 2 file containing: corrected Ocean elevations above the reference ellipsoid, surface roughness, reflectance, and the corrections that were used. The product parameters are the result of product-specialized waveform fitting.
ShortName	GLAH15
VersionID	34

/METADATA/COLLECTIONMETADATA/ContactOrganization

Attribute	Example Value
Data_Originator	ContactOrganizationContainer
Archive	ContactOrganizationContainer

/METADATA/COLLECTIONMETADATA/ContactOrganization/Archive

Attribute	Example Value
Role	Archive
HoursofService	M-F, 8:00am to 5:00pm, Mountain Time
ContactInstructions	For inquiries, contact NSIDC User Services. Primary first level contact.
ContactOrganizationName	NSIDC User Services
StreetAddress	CIRES/NSIDC University of Colorado Campus, Box 449
City	Boulder
StateProvince	Colorado
PostalCode	80309-0449

Attribute	Example Value
Country	USA
TelephoneNumber	303-492-2468
TelephoneNumberType	Facsimile
ElectronicMailAddress	nsidc@nsidc.org

/METADATA/COLLECTIONMETADATA/ContactOrganization/Data_Originator

Attribute	Example Value
Role	Data Originator
HoursofService	M-F, 8:00am to 4:30pm Eastern Time
ContactInstructions	Contact by e-mail first
ContactOrganizationName	ICESat Science Investigator-led Processing System (I-SIPS)
StreetAddress	Building 33, NASA Goddard Space Flight Center
City	Greenbelt
StateProvince	Maryland
PostalCode	20771
Country	USA
TelephoneNumber	757-864-1238
TelephoneNumberType	Voice
ElectronicMailAddress	David.W.Hancock@nasa.gov

/METADATA/COLLECTIONMETADATA/ContactPerson

Attribute	Example Value
Hancock	ContactPersonContainer
Schutz	ContactPersonContainer
Zwally	ContactPersonContainer
DiMarzio	ContactPersonContainer

/METADATA/COLLECTIONMETADATA/ContactPerson/DiMarzio

Attribute	Example Value
Role	Producer
HoursofService	M-F, 8:00am to 4:30pm Eastern Time

Attribute	Example Value
ContactInstructions	None
ContactJobPosition	Deputy Science Software Development Manager
ContactFirstName	John
ContactMiddleName	P
ContactLastName	DiMarzio
StreetAddress	Building 33, Rm. B-209D, NASA/GSFC
City	Greenbelt
StateProvince	Maryland
PostalCode	20771
Country	USA
TelephoneNumber	301-614-5893
TelephoneNumberType	Voice
ElectronicMailAddress	John.P.Dimarzio.1@nasa.gov

/METADATA/COLLECTIONMETADATA/ContactPerson/Hancock

Attribute	Example Value
Role	Data Originator
HoursofService	M-F, 8:00am to 4:30pm. Eastern Time.
ContactInstructions	None
ContactJobPosition	Science Software Development Manager.
ContactFirstName	David
ContactMiddleName	W.
ContactLastName	Hancock
StreetAddress	Building N-159, NASA/GSFC Wallops Flight Facility.
City	Wallops Island
StateProvince	Virginia
PostalCode	23337
Country	USA
TelephoneNumber	757-824-1238

Attribute	Example Value
TelephoneNumberType	Voice
ElectronicMailAddress	David.W.Hancock@nasa.gov

/METADATA/COLLECTIONMETADATA/ContactPerson/Schutz

Attribute	Example Value
Role	Investigator
HoursofService	M-F, 8:00am to 4:30pm Central Time
ContactInstructions	None
ContactJobPosition	GLAS Science Team Leader
ContactFirstName	Bob
ContactMiddleName	E
ContactLastName	Schutz
StreetAddress	3925 W. Braker Lane, Center for Space Research
City	Austin
StateProvince	Texas
PostalCode	78759-5321
Country	USA
TelephoneNumber	512-471-4267
TelephoneNumberType	Voice
ElectronicMailAddress	schutz@utcsr.ae.utexas.edu

/METADATA/COLLECTIONMETADATA/ContactPerson/Zwally

Attribute	Example Value
Role	Producer
HoursofService	M-F, 8:00am to 4:30pm Eastern Time
ContactInstructions	None.
ContactJobPosition	ICESat Project Scientist
ContactFirstName	Jay
ContactLastName	Zwally
StreetAddress	Building 33, Rm A-217

Attribute	Example Value
City	Greenbelt
StateProvince	Maryland
PostalCode	20771
Country	USA
TelephoneNumber	301-614-5643
TelephoneNumberType	Voice
ElectronicMailAddress	Jay.Zwally@nasa.gov

/METADATA/COLLECTIONMETADATA/DisciplineTopicParameters

Attribute	Example Value
Land_Surface	DisciplineTopicParametersContainer

/METADATA/COLLECTIONMETADATA/DisciplineTopicParameters/Land_Surface

Attribute	Example Value
ECSDisciplineKeyword	Earth Science
ECSTopicKeyword	Land Surface
ECSTermKeyword	Surface Radiative Properties
ECSVariableKeyword	Reflectance

/METADATA/COLLECTIONMETADATA/DisciplineTopicParameters/Land_Surface/ECSPParameter

Attribute	Example Value
ECSPParameterKeyword	Laser Reflectance

/METADATA/COLLECTIONMETADATA/ECSCollection

Attribute	Example Value
RevisionDate	2013-11-07
SuggestedUsage	GLAH14 contains GLAS land elevation data that includes geolocation and reflectance plus the geodetic, instrument, and atmospheric corrections used. Parameters are at the full 40Hz resolution for locations that fall within the ICESat land mask. Each GLAH14 file was created from an equivalent GLA14 binary file. The data used to create the GLAH14 values are contained in the equivalent GLAHxx files for the GLAxx files. See the provenance metadata for the creation of the GLA14.
ProcessingCenter	GSFC I-SIPS
ArchiveCenter	NSIDC

Attribute	Example Value
VersionDescription	GLASHDF V2.0-Elevations for all products except GLAH14 are now based on the range from the Gaussian fit to the transmit pulse to the Gaussian fit to the received echo. Range used for trop corrections was changed from threshold to centroid.(See Rel Notes)
DatasetDisclaimerPointer	https://nsidc.org/data/icesat/disclaimer.html
ECSCollectionGuidePointer	https://nsidc.org/data/glah01-glah05-glah06-glah12-glah13-glah14-glah15/versions/34/documentation
ECSCollectionGuidePointerComment	Guide Document for this product at NSIDC
MiscellaneousInformationPointer	https://nsidc.org/data/icesat/
MiscellaneousInformationPointerComment	GLAS Product page at NSIDC

/METADATA/COLLECTIONMETADATA/Platform

Attribute	Example Value
ICESat	PlatformContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat

Attribute	Example Value
PlatformShortName	ICESat
PlatformLongName	Ice, Cloud, and Land Elevation Satellite
PlatformType	Spacecraft

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument

Attribute	Example Value
GLAS	InstrumentContainer
GPS	InstrumentContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS

Attribute	Example Value
InstrumentShortName	GLAS
InstrumentLongName	Geoscience Laser Altimeter System
InstrumentTechnique	Laser Altimetry and Light Detection and Radar
NumberofSensors	3

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/InstrumentCharacteristic

Attribute	Example Value
-----------	---------------

Attribute	Example Value
SwathWidth	InstrumentCharacteristicContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/InstrumentCharacteristic/SwathWidth

Attribute	Example Value
InstrumentCharacteristicName	SwathWidth
InstrumentCharacteristicDescription	The width of the sensor scan as the satellite moves along the ground track.
InstrumentCharacteristicDataType	int
InstrumentCharacteristicUnit	kilometers
InstrumentCharacteristicValue	2

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor

Attribute	Example Value
LA	SensorContainer
PC	SensorContainer
CD	SensorContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/CD

Attribute	Example Value
SensorShortName	CD
SensorLongName	Cloud LIDAR
SensorTechnique	Measure of 1064nm return energy in 75m bins from 20km to surface

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/CD/SensorCharacteristic

Attribute	Example Value
wavelength	SensorCharacteristicContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/CD/SensorCharacteristic/wavelength

Attribute	Example Value
SensorCharacteristicName	wavelength
SensorCharacteristicDescription	detector
SensorCharacteristicDataType	varchar
SensorCharacteristicUnit	nanometer

Attribute	Example Value
SensorCharacteristicValue	1064 nm

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/LA

Attribute	Example Value
SensorShortName	LA
SensorLongName	Laser Altimeter
SensorTechnique	Exact Measurement of Time between Transmit Pulse and receive ground return

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/LA/SensorCharacteristic

Attribute	Example Value
wavelength	SensorCharacteristicContainer
waveform	SensorCharacteristicContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/LA/SensorCharacteristic/waveform

Attribute	Example Value
SensorCharacteristicName	waveform
SensorCharacteristicDescription	digitizer
SensorCharacteristicDataType	varchar
SensorCharacteristicUnit	counts
SensorCharacteristicValue	0-255

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/LA/SensorCharacteristic/wavelength

Attribute	Example Value
SensorCharacteristicName	wavelength
SensorCharacteristicDescription	transmission
SensorCharacteristicDataType	varchar
SensorCharacteristicUnit	nanometer
SensorCharacteristicValue	1064 nm

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/PC

Attribute	Example Value
SensorShortName	PC

Attribute	Example Value
SensorLongName	Photon Counter for the 532 nm Aerosol Returns
SensorTechnique	Counting of 532nm photon return in 75m bins 40km to surface

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/PC/SensorCharacteristic

Attribute	Example Value
wavelength	SensorCharacteristicContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GLAS/Sensor/PC/SensorCharacteristic/wavelength

Attribute	Example Value
SensorCharacteristicName	wavelength
SensorCharacteristicDescription	detector
SensorCharacteristicDataType	varchar
SensorCharacteristicUnit	nanometer
SensorCharacteristicValue	532nm

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GPS

Attribute	Example Value
InstrumentShortName	GPS
InstrumentLongName	Global Positioning System Receiver
InstrumentTechnique	Radionavigation
NumberofSensors	1

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GPS/Sensor

Attribute	Example Value
GPS_Receiver	SensorContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/Instrument/GPS/Sensor/GPS_Receiver

Attribute	Example Value
SensorShortName	GPS Receiver
SensorLongName	Dual frequency GPS receiver
SensorTechnique	Pseudorange and carrier phase

/METADATA/COLLECTIONMETADATA/Platform/ICESat/PlatformCharacteristic

Attribute	Example Value
-----------	---------------

Attribute	Example Value
OrbitInclination	PlatformCharacteristicContainer
OrbitalPeriod	PlatformCharacteristicContainer

/METADATA/COLLECTIONMETADATA/Platform/ICESat/PlatformCharacteristic/OrbitInclination

Attribute	Example Value
PlatformCharacteristicName	OrbitInclination
PlatformCharacteristicDescription	Angle between the orbit plane and the Earth's equatorial plane
PlatformCharacteristicDataType	float
PlatformCharacteristicUnit	Degrees
PlatformCharacteristicValue	94.0

/METADATA/COLLECTIONMETADATA/Platform/ICESat/PlatformCharacteristic/OrbitalPeriod

Attribute	Example Value
PlatformCharacteristicName	OrbitalPeriod
PlatformCharacteristicDescription	Orbital period in decimal minutes.
PlatformCharacteristicDataType	float
PlatformCharacteristicUnit	Minutes
PlatformCharacteristicValue	96.7

/METADATA/COLLECTIONMETADATA/ProcessingLevel

Attribute	Example Value
ProcessingLevelDescription	Geophysical Quantities at the sensor resolution or geolocated
ProcessingLevelID	2

/METADATA/COLLECTIONMETADATA/Review

Attribute	Example Value
ScienceReviewDate	2001-03-04
ScienceReviewStatus	QA at DAACs
FutureReviewDate	2001-09-04

/METADATA/COLLECTIONMETADATA/Spatial

Attribute	Example Value
-----------	---------------

Attribute	Example Value
SpatialCoverageType	Horizontal
WestBoundingCoordinate	-180.0
NorthBoundingCoordinate	90.0
EastBoundingCoordinate	180.0
SouthBoundingCoordinate	-90.0

/METADATA/COLLECTIONMETADATA/StorageMediumClass

Attribute	Example Value
StorageMedium	Online

/METADATA/COLLECTIONMETADATA/Temporal

Attribute	Example Value
TimeType	UTC
DateType	J2000
TemporalRangeType	Continuous Range
PrecisionofSeconds	2
EndsatPresentFlag	Y
RangeBeginningDate	2003-01-13
RangeBeginningTime	00:00:00
RangeEndingDate	2010-01-13
RangeEndingTime	00:00:00

/METADATA/INVENTORYMETADATA

Attribute	Example Value
PGEVersion	Version 1.4
ShortName	GLAH14
VersionID	34
RangeBeginningTime	01:51:38
RangeEndingTime	00:24:44
RangeBeginningDate	2003-11-18
RangeEndingDate	2003-11-19

/METADATA/INVENTORYMETADATA/ECSDataGranule

Attribute	Example Value
ReprocessingPlanned	no further update anticipated
ReprocessingActual	reprocessed
LocalGranuleID	GLAH14_634_2103_002_0407_0_01_0001.H5
ProductionDateTime	2014-08-18T21:11:22
LocalVersionID	634

/METADATA/INVENTORYMETADATA/InputGranule

Attribute	Example Value
InputPointer	CTL00_000_20140818_2598059_01_gla14_h5_convert.ctl, tai-utc.dat, GLA14_634_2103_002_0407_0_01_0001.DAT, DsESDTG1GLAH14.034.desc

/METADATA/INVENTORYMETADATA/MeasuredParameter

Attribute	Example Value
ParameterName	Surface_Elevation, Surface_Reflectance

/METADATA/INVENTORYMETADATA/OrbitCalculatedSpatialDomain

Attribute	Example Value
OrbitNumber	4604, 4605, 4606, 4607, 4608, 4609, 4610, 4611, 4612, 4613, 4614, 4615, 4616, 4617, 4618
StartOrbitNumber	4604
StopOrbitNumber	4618
EquatorCrossingLongitude	-103.22287, -127.41792, -151.61336, -175.8089, 159.99582, 135.80128, 111.6064, 87.41001, 63.21418, 39.01927, 14.825027, -9.368591, -33.562866, -57.758118, -81.95212
EquatorCrossingTime	01:38:10, 03:14:50, 04:51:29, 06:28:07, 08:04:46, 09:41:25, 11:18:05, 12:54:44, 14:31:22, 16:08:02, 17:44:42, 19:21:21, 20:58:00, 22:34:38, 00:11:17
EquatorCrossingDate	2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-18, 2003-11-19

/METADATA/INVENTORYMETADATA/ProductSpecificMetadata

Attribute	Example Value
PercentGroundHit	0
OrbitQuality	6
Track	407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421
Instrument_State	373338

Attribute	Example Value
Timing_Bias	0
Timing_Drift	0
ReferenceOrbit	1
SP_ICE_PATH_NO	3429, 3430, 3431, 3432, 3433, 3434, 3435, 3436, 3437, 3438, 3439, 3440, 3441, 3442, 3443
SP_ICE_GLAS_StartBlock	NOT SET
SP_ICE_GLAS_EndBlock	NOT SET
Cycle	2
Instance	3
Range_Bias	0
Instrument_State_Date	2003-10-30
Instrument_State_Time	00:00:00
Range_Bias_Date	2003-10-30
Range_Bias_Time	00:00:00
Timing_Bias_Date	2003-10-30
Timing_Bias_Time	00:00:00
identifier_product_doi	10.5067/ICESAT/GLAS/DATA211
identifier_file_uuid	2e672450-982e-43a3-ad9a-65c360d51ad4
identifier_product_doi_authority	http://dx.doi.org/10.5067/ICESAT/GLAS/DATA211

/METADATA/PROVENANCE

/METADATA/PROVENANCE/STEP_1

Attribute	Example Value
ProcessDateTime	2014-05-24T04:16:41

/METADATA/PROVENANCE/STEP_1/ProcessAgent

Attribute	Example Value
Name	glas_alt
Type	2
Version	6.1
Description	This process is an instantiation of the GLAS Science Algorithm Software (GSAS) 2 ATBDs.

Attribute	Example Value
Name	./CTL00_000_20140818_2598059_01_gla14_h5_convert.ct1, ./tai-utc.dat, ./GLA14_634_2103_002_0407_0_01_0001.DAT, ./DsESDTGLGLAH14.034.desc
Type	IN_CNTL, IN_ANC_TAIUTC, IN_GLA14, IN_ESDT
Version	0, 0, 1, 1

/METADATA/PROVENANCE/STEP_2/ProcessOutput

Attribute	Example Value
Name	./GLAH14_634_2103_002_0407_0_01_0001.H5
Type	OUT_GLAH14
Version	1
UUID	2e672450-982e-43a3-ad9a-65c360d51ad4
DOI	10.5067/ICESAT/GLAS/DATA211

Page last updated: 09/03/14

