



ATLAS/ICESat-2 L3B Daily and Monthly Gridded Sea Ice Freeboard, Version 1

USER GUIDE

How to Cite These Data

As a condition of using these data, you must include a citation:

Petty, A. A., R. Kwok, M. Bagnardi, A. Ivanoff, N. Kurtz, J. Lee, J. Wimert, D. Hancock. 2020. ATLAS/ICESat-2 L3B Daily and Monthly Gridded Sea Ice Freeboard, Version 1. [Indicate subset used]. Boulder, Colorado USA. NASA National Snow and Ice Data Center Distributed Active Archive Center. <https://doi.org/10.5067/ATLAS/ATL20.001>. [Date Accessed].

FOR QUESTIONS ABOUT THESE DATA, CONTACT NSIDC@NSIDC.ORG

FOR CURRENT INFORMATION, VISIT <https://nsidc.org/data/ATL20>



National Snow and Ice Data Center

TABLE OF CONTENTS

1	DATA DESCRIPTION	2
1.1	Parameters	2
1.2	File Information.....	2
1.2.1	Format.....	2
1.2.2	File Contents.....	2
1.2.3	Data Groups.....	2
1.2.4	Naming Convention	4
1.2.5	Browse File	4
1.3	Spatial Information.....	5
1.3.1	Coverage	5
1.3.2	Resolution.....	5
1.3.3	Geolocation.....	5
1.4	Temporal Information	6
1.4.1	Coverage	6
1.4.2	Resolution.....	6
2	DATA ACQUISITION AND PROCESSING.....	7
2.1	Background	7
2.2	Acquisition	7
2.3	Processing.....	7
2.4	Quality, Errors, and Limitations	8
3	VERSION HISTORY	9
4	RELATED DATA SETS.....	9
5	RELATED WEBSITES	9
6	CONTACTS AND ACKNOWLEDGMENTS	9
7	DOCUMENT INFORMATION.....	10
7.1	Publication Date	10
7.2	Date Last Updated.....	10
	APPENDIX A: ATLAS/ICESAT-2 DESCRIPTION	11

1 DATA DESCRIPTION

1.1 Parameters

This data set contains daily and monthly gridded estimates of sea ice freeboard, derived from along-track freeboard estimates in the ATLAS/ICESat-2 L3A Sea Ice Freeboard product ([ATL10, V3](#)).

1.2 File Information

1.2.1 Format

Data are provided as HDF5 formatted files. HDF is a data model, library, and file format designed specifically for storing and managing data. For more information about HDF, visit the [HDF Support Portal](#).

1.2.2 File Contents

Data files contain gridded freeboard for two time-spans: daily and monthly.

1.2.3 Data Groups

Within data files, similar variables such as science data, instrument parameters, and metadata are grouped together according to the HDF model. The following figure shows data groups and variables stored at the top level in ATL20 data files:




Figure 1. ATL20 Top-Level Data Groups and Variables

The following sections describe the data groups and their contents plus the variables stored at the top level in ATL20 data files:

1.2.3.1 METADATA

ISO19115 structured summary metadata.

1.2.3.2 ancillary_data

Information ancillary to the data product such as product and instrument characteristics and processing constants.

1.2.3.3 daily

Subfolders, one for each day of the month, that contain the day's gridded mean freeboard (mean_fb), values used to compute the daily mean freeboard, and daily standard deviation.

1.2.3.4 monthly

Monthly gridded freeboard, values used to compute the monthly freeboard, and the monthly standard deviation.

1.2.3.5 orbit_info

Orbit parameters that are constant for a granule, such as the RGT number, cycle, and spacecraft orientation.

1.2.3.6 quality_assessment

Quality assessment data for the granule as a whole, including a pass/fail flag and a failure reason indicator.

The following variables are stored at the top level of ATL20 data files alongside the data groups described above:

- crs: metadata describing the coordinate reference system
- grid_lat: latitude at the center of each grid cell
- grid_lon: longitude at the center of each grid cell
- grid_x: x value at the center of each grid cell
- grid_y: y value at the center of each grid cell
- land_mask_map: flags for each grid cell denoting land (1) or ocean/sea ice (0)

For additional information, see the following Technical References on the [ATL20 data set landing page](#):

- ATL20 Data Dictionary (complete list of variables stored)
- “Appendix C: ATL20 Gridded Freeboard,” ATBD for Sea Ice Products

1.2.4 Naming Convention

Data files utilize the following naming convention:

Example:

```
ATL20-01_20190301004639_09560201_001_01.h5
ATL20-02_20190301004639_09560201_001_01.h5
ATL20-[HH]_[yyyymmdd][hhmmss]_[tttccss]_[vvv_rr].h5
```

Variable	Description
ATL20	ATLAS/ICESat-2 L3B Daily and Monthly Gridded Sea Ice Freeboard product
HH	Hemisphere code. Northern Hemisphere = 01, Southern Hemisphere = 02
yyyymmdd	Year, month, and day of data acquisition
hhmmss	Data acquisition start time, hour, minute, and second (UTC)
tttt	Four digit Reference Ground Track number. The ICESat-2 mission has 1,387 RGTs, numbered from 0001 to 1387.
cc	Cycle Number. Each of the 1387 RGTs is targeted in the polar regions once every 91 days. The cycle number tracks the number of 91-day periods that have elapsed since ICESat-2 entered the science orbit.
ss	Segment number. Not used. Always 01.
vvv_rr	Version and revision number*

*NOTE: From time to time, NSIDC receives duplicate, reprocessed granules from our data provider. These granules have the same file name as the original (i.e. date, time, ground track, cycle, and segment number), but the revision number has been incremented. Although NSIDC deletes the superceded granule, the process can take several days. As such, if you encounter multiple granules with the same file name, please use the granule with the highest revision number.

Each data file has a corresponding XML file that contains additional science metadata. XML metadata files have the same name as their corresponding .h5 file, but with .xml appended.

1.2.5 Browse File

An HDF5 browse file is provided for each granule that contains a composite image of the monthly freeboard.

1.3 Spatial Information

1.3.1 Coverage

Coverage is global; however, the input ATL10 freeboards are only reported where ice concentration is >50%.

1.3.2 Resolution

25 km

1.3.3 Geolocation

Data are mapped on a planimetric grid using the SSM/I Polar Stereographic Projection.

Table 1. Northern Hemisphere Projection Details

Geographic coordinate system	Unspecified datum based upon the Hughes 1980 ellipsoid
Projected coordinate system	NSIDC Sea Ice Polar Stereographic North
Longitude of true origin	-45°
Latitude of true origin	0°
Scale factor at longitude of true origin	1
Datum	Not_specified_based_on_Hughes_1980_ellipsoid
Ellipsoid/spheroid	Hughes 1980
Units	Meters
False easting	0
False northing	0
EPSG code	3411
PROJ4 string	+proj=stere +lat_0=90 +lat_ts=70 +lon_0=-45 +k=1 +x_0=0 +y_0=0 +a=6378273 +b=6356889.449 +units=m +no_defs
Reference	https://epsg.io/3411

Table 2. Southern Hemisphere Projection Details

Geographic coordinate system	Unspecified datum based upon the Hughes 1980 ellipsoid
Projected coordinate system	NSIDC Sea Ice Polar Stereographic North
Longitude of true origin	0°
Latitude of true origin	-70°

Scale factor at longitude of true origin	1
Datum	Not_specified_based_on_Hughes_1980_ellipsoid
Ellipsoid/spheroid	Hughes 1980
Units	Meters
False easting	0
False northing	0
EPSG code	3411
PROJ4 string	+proj=stere +lat_0=-90 +lat_ts=-70 +lon_0=0 +k=1 +x_0=0 +y_0=0 +a=6378273 +b=6356889.449 +units=m +no_defs
Reference	https://epsg.io/3412

Table 3. Grid Details

Hemisphere	North	South
Grid cell size (x, y pixel dimensions)	25 km, 25 km	25 km, 25 km
Number of rows	448	332
Number of columns	304	316
Geolocated lower left point in grid	~30.89° N ~168.35° W	~39.23° S ~317.16° W
Nominal gridded resolution	25 km	25 km
Grid rotation	N/A	N/A
ulxmap – x-axis map coordinate of the center of the upper-left pixel (XLLCORNER for ASCII data)	-3850 projected km	-3950 projected km
ulymap – y-axis map coordinate of the center of the upper-left pixel (YLLCORNER for ASCII data)	5850 projected km	4350 projected km

1.4 Temporal Information

1.4.1 Coverage

1 November 2018 to 01 November 2020

1.4.2 Resolution

Two resolutions are provided: daily and monthly. Months are defined as the first through the last day of each calendar month.

2 DATA ACQUISITION AND PROCESSING

The following sections refer to the Ice, Cloud, and Land Elevation Satellite (ICESat-2) Project Algorithm Theoretical Basis Document (ATBD) for Sea Ice Products. This ATBD provides detailed descriptions of the following ATLAS/ICESat-2 products:

- ATLAS/ICESat-2 L3A Sea Ice Height (ATL07)
- ATLAS/ICESat-2 L3A Sea Ice Freeboard (ATL10)
- ATLAS/ICESat-2 L3B Daily and Monthly Gridded Sea Ice Freeboard (ATL20)
- ATLAS/ICESat-2 L3B Daily and Monthly Gridded Sea Surface Height – Ice-Covered Ocean (ATL21)

To obtain the ATBD for Sea Ice Products, see Technical References on the [ATL20 data set landing page](#).

2.1 Background

The ATL10 product identifies leads* in sea ice and establishes a reference sea surface used to estimate along-track freeboard heights. ATL20 aggregates ATL10 along-track freeboard estimates and computes daily and monthly gridded freeboard in NSIDC Polar Stereographic Northern and Southern Hemisphere 25 km grids.

*Leads are narrow, linear cracks in sea ice that form when separate patches of floating ice diverge or shear as they move parallel to each other.

2.2 Acquisition

The ATL20 algorithm inputs ATL10 granules and computes gridded daily and monthly freeboard as described in the following section.

2.3 Processing

To compute daily freeboard estimates, the algorithm collects all the ATL10 individual strong beam freeboard beam segments from the time span of interest and performs the following calculations.

Daily

For for each 25 km grid cell (x, y, D), where D is day-of-month, the algorithm calculates the mean length, freeboard, and standard deviation as follows:

$$\bar{L}(x, y, D) = \sum_N^i L_s^i$$

$$\bar{h}(x, y, D) = \frac{\sum_N L_s^i h_s^i}{\sum_N L_s^i}$$

$$\sigma^2(x, y, D) = \frac{\sum_N L_s^i (h_s^i)^2}{\sum_N L_s^i}$$

$N(x, y, D) = \text{number of segments}$

In the equations above, h is the segment freeboard for segment i , L is the associated segment length, and N is the population count.

Monthly

Monthly gridded freeboard is computed from the daily composites as follows:

$$\bar{L}_M(x, y) = \sum_D \bar{L}(x, y, d)$$

$$\bar{h}_M(x, y) = \frac{\sum_D \bar{h}(x, y, d) \bar{L}(x, y, d)}{\sum_D \bar{L}(x, y, d)}$$

$$\sigma_M^2(x, y) = \frac{\sum_D \bar{L}(x, y, d) (\sigma^2(x, y, d) + \bar{h}^2(x, y, d))}{\sum_D \bar{L}(x, y, d)} - \bar{h}_M^2(x, y)$$

$$N_M(x, y) = \sum_D N(x, y, D)$$

Additional information about how ATL20 is constructed is available in “Section 6.2 | Dataflow and procedural steps (ATL20)” in the ATBD for Sea Ice Products.

2.4 Quality, Errors, and Limitations

Errors in the ATLAS/ICESat-2 height retrievals can arise from a variety of sources, including:

- Sampling error (heights reflect random point sample of the height distribution)
- Background noise from random non-signal photon returns
- Misidentified signal photons
- Atmospheric forward scattering delays
- Subsurface scattering within ice or snow
- First-photon bias (inherent with photon-counting detectors)

These errors in ATLAS/ICESat-2 upstream products can propagate into ATL20. Error sources, their impacts, and mitigation strategies are discussed throughout the ATBD for Sea Ice Products. See “Section 2.2.5 | Potential error sources” for an overview.

3 VERSION HISTORY

Version 1 (November 2020).

Note: Version 1 of this data set was derived from Version 3 of ATL10.

4 RELATED DATA SETS

- [ATLAS/ICESat-2 L3A Sea Ice Height \(ATL07\)](#)
- [ATLAS/ICESat-2 L3A Sea Ice Freeboard \(ATL10\)](#)

5 RELATED WEBSITES

- [Polar Stereographic Data | NSIDC Polar Stereographic Grid Definitions](#)

6 CONTACTS AND ACKNOWLEDGMENTS

Alek Petty

NASA Goddard Space Flight Center
Greenbelt, MD 20771

Ron Kwok

Jet Propulsion Laboratory
California Institute of Technology
Pasadena, CA 91109

Marco Bagnardi

NASA Goddard Space Flight Center
Greenbelt, MD 20771

Alvaro Ivanoff

ADNET Systems, Inc.
NASA Goddard Space Flight Center
Greenbelt, MD 20771

Nathan Kurtz

NASA Goddard Space Flight Center
Greenbelt, MD 20771

Jeff Lee

NASA Goddard Space Flight Center
Greenbelt, MD 20771

Jesse Wimert

Stinger Ghaffarian Technologies, Inc
NASA Goddard Space Flight Center
Greenbelt, MD 20771

David Hancock

NASA Goddard Space Flight Center
Greenbelt, MD 20771

7 DOCUMENT INFORMATION

7.1 Publication Date

November 2020

7.2 Date Last Updated

January 2022

APPENDIX A: ATLAS/ICESAT-2 DESCRIPTION

The ATLAS instrument and ICESat-2 observatory utilize a photon-counting lidar and ancillary systems (GPS and star cameras) to measure the time a photon takes to travel from ATLAS to Earth and back again and to determine the photon's geodetic latitude and longitude. Laser pulses from ATLAS illuminate three left/right pairs of spots on the surface that as ICESat-2 orbits Earth trace out six ground tracks that are typically about 14 m wide. Each ground track is numbered according to the laser spot number that generates it, with ground track 1L (GT1L) on the far left and ground track 3R (GT3R) on the far right. Left/right spots within each pair are approximately 90 m apart in the across-track direction and 2.5 km in the along-track direction. The ATL06 data product is organized by ground track, with ground tracks 1L and 1R forming pair one, ground tracks 2L and 2R forming pair two, and ground tracks 3L and 3R forming pair three. Each pair also has a Pair Track—an imaginary line halfway between the actual location of the left and right beams (see figures 1 and 2). Pair tracks are approximately 3 km apart in the across-track direction.

The beams within each pair have different transmit energies—so-called weak and strong beams—with an energy ratio between them of approximately 1:4. The mapping between the strong and weak beams of ATLAS, and their relative position on the ground, depends on the orientation (yaw) of the ICESat-2 observatory, which is changed approximately twice per year to maximize solar illumination of the solar panels. The forward orientation corresponds to ATLAS traveling along the +x coordinate in the ATLAS instrument reference frame (see Figure A1). In this orientation, the weak beams lead the strong beams and a weak beam is on the left edge of the beam pattern. In the backward orientation, ATLAS travels along the -x coordinate, in the instrument reference frame, with the strong beams leading the weak beams and a strong beam on the left edge of the beam pattern (see Figure A2). The first yaw flip was performed on December 28, 2018, placing the spacecraft into the backward orientation. The current spacecraft orientation, as well as a history of previous yaw flips, is available in the [ICESat-2 Major Activities](#) tracking document (.xlsx).

The Reference Ground Track (RGT) refers to the imaginary track on Earth at which a specified unit vector within the observatory is pointed. Onboard software aims the laser beams so that the RGT is always between ground tracks 2L and 2R (i.e. coincident with Pair Track 2). The ICESat-2 mission acquires data along 1,387 different RGTs. Each RGT is targeted in the polar regions once every 91 days (i.e. the satellite has a 91-day repeat cycle) to allow elevation changes to be detected. Cycle numbers track the number of 91-day periods that have elapsed since the ICESat-2 observatory entered the science orbit. RGTs are uniquely identified by appending the two-digit cycle number to the RGT number, e.g. 000103 (RGT 0001, cycle 03) or 138705 (RGT 1387, cycle 05).

Users should note that between 14 October 2018 and 30 March 2019 the spacecraft pointing control was not yet optimized. As such, ICESat-2 data acquired during that time do not lie along the

nominal RGTs, but are offset at some distance from the RGTs. Although not along the RGT, the geolocation information for these data is not degraded.




Figure A1. Spot and ground track (GT) naming convention with ATLAS oriented in the forward (instrument coordinate +x) direction.




Figure A2. Spot and ground track (GT) naming convention with ATLAS oriented in the backward (instrument coordinate -x) direction.