



# MODIS/Terra Snow Cover 8-Day L3 Global 0.05Deg CMG, Version 5

---

## USER GUIDE

### How to Cite These Data

As a condition of using these data, you must include a citation:

Hall, D. K., V. V. Salomonson, and G. A. Riggs. 2006. *MODIS/Terra Snow Cover 8-Day L3 Global 0.05Deg CMG, Version 5*. [Indicate subset used]. Boulder, Colorado USA. NASA National Snow and Ice Data Center Distributed Active Archive Center. <https://doi.org/10.5067/6PMGAHFLY5EV>. [Date Accessed].

FOR QUESTIONS ABOUT THESE DATA, CONTACT [NSIDC@NSIDC.ORG](mailto:NSIDC@NSIDC.ORG)

FOR CURRENT INFORMATION, VISIT <https://nsidc.org/data/MOD10C2>



National Snow and Ice Data Center

# TABLE OF CONTENTS

1	DETAILED DATA DESCRIPTION .....	3
1.1	Format.....	3
1.1.1	External Metadata File.....	5
1.2	File Naming Convention.....	5
1.3	File Size .....	5
1.4	Spatial Coverage.....	6
1.4.1	Spatial Resolution.....	6
1.4.2	Projection.....	6
1.4.3	Grid.....	6
1.5	Temporal Coverage .....	6
1.5.1	Temporal Resolution .....	6
1.6	Parameter or Variable .....	7
1.6.1	Parameter Description.....	7
1.6.2	Parameter Range .....	7
2	SOFTWARE AND TOOLS.....	7
2.1	Data Access Aids.....	7
2.2	Data Analysis Tools .....	8
3	DATA ACQUISITION AND PROCESSING .....	8
3.1	Theory of Measurements .....	8
3.2	Data Acquisition Methods .....	8
3.2.1	Source or Platform Mission Objectives.....	8
3.2.2	MODIS Snow and Sea Ice Global Mapping Project Objectives.....	9
3.2.3	Data Collection System .....	9
3.2.4	Data Acquisition and Processing.....	9
3.3	Derivation Techniques and Algorithms.....	10
3.3.1	Processing Steps.....	10
3.3.2	Error Sources .....	10
3.4	Quality Assessment .....	11
3.5	Sensor or Instrument Description.....	11
3.5.1	Principles of Operation .....	11
3.5.2	Technical Specifications.....	12
3.5.3	Spectral Bands .....	12
3.5.4	Sensor or Instrument Measurement Geometry.....	12
3.5.5	Manufacturer of Sensor or Instrument.....	12
3.5.6	Calibration .....	13
4	REFERENCES AND RELATED PUBLICATIONS .....	13
4.1	Related Data Collections.....	15
5	CONTACTS AND ACKNOWLEDGMENTS.....	15
5.1	Principle Investigators .....	15

6	DOCUMENT INFORMATION .....	16
6.1	Publication Date .....	16
6.2	Date Last Updated .....	16

# 1 DETAILED DATA DESCRIPTION

This data set contains snow cover and Quality Assessment (QA) data, latitudes and longitudes in compressed Hierarchical Data Format-Earth Observing System (HDF-EOS) format, and corresponding metadata. MOD10C2 consists of 7200 columns by 3600 rows of global arrays of snow cover in a 0.05 degree Climate Modeling Grid (CMG). MODIS snow cover data are based on a snow mapping algorithm that employs a Normalized Difference Snow Index (NDSI) and other criteria tests. No major changes were made to this Version, V005, of the data set.

Please visit the following sites for more information about the V005 data, known data problems, production schedule, and future plans:

- [MODIS Snow Products User Guide to Collection 5](#)
- [NASA Goddard Space Flight Center: MODIS Adaptive Processing System \(MODAPS\) Services](#)
- [The MODIS Snow and Sea Ice Global Mapping Project: Project Description](#)
- [NASA Goddard Space Flight Center: MODIS Land Quality Assessment](#)
- [MODIS Land Team Validation: Status for Snow Cover/Sea Ice: MOD10/29](#)

This data set is retired and no longer available for download. The most up-to-date version of this data can be accessed on the NSIDC website [here](#).



Algorithms that generate snow cover products are continually being improved as limitations become apparent in early versions of data. As a new algorithm becomes available, a new version of data is released. Users are encouraged to work with the most current version of MODIS data available, which is the highest version number.

## 1.1 Format

---

MODIS snow products are archived in compressed HDF-EOS format, which employs point, swath, and grid structures to geolocate the data fields to geographic coordinates. This data compression should be transparent to most users since HDF capable software tools automatically uncompress the data. Various software packages, including several in the public domain, support the HDF-EOS data format. See section 2.0 Software and Tools for details. Also, see the [Hierarchical Data Format - Earth Observing System \(HDF-EOS\) Web site](#) for more information about the HDF-EOS data format, as well as tutorials in uncompressing the data and converting data to binary format.

Data can also be obtained in GeoTIFF format from [Reverb | ECHO](#), NASA's Next Generation Earth Science Discovery Tool.

MOD10C2 V005 consists of 7200 columns by 3600 rows of global arrays of snow cover. The MOD10C2 product was created by merging all of the MOD10A2 tiles for an eight-day period and binning the 500 m data to the 0.05 degree spatial resolution of the CMG cells. Each data granule contains the following HDF-EOS local attribute fields, which are stored with their associated Scientific Data Set (SDS).

Each data granule also contains metadata either stored as global attributes or as HDF-predefined fields, which are stored with each SDS.

The Eight Day CMG Snow Cover field is a global map of snow cover extent expressed as a percentage of land in each CMG cell for an eight-day period. Snow percentage in each cell of the Day CMG Snow Cover field is calculated using 500 m totals of the number of snow observations and count of land observations in that cell for the day. The percentage of snow-covered land is based on the clear-sky view of land in the CMG cell. So the amount of snow observed in a CMG cell is based on the cloud-free observations mapped into the CMG grid cell for all land in that cell.

$$\text{percent snow} = 100 * \text{count of snow observations} / \text{count of land}$$

In V005 data, snow cover ranges from 0 -100 percent.

The Eight Day CMG Confidence Index field indicates how much of the land surface MODIS observes. The index represents an estimate of confidence in each cell's data value and indicates how confident the algorithm is that snow percentage in a cell is correct based on which data: snow, snow-free land, cloud, or unknown, were binned into the grid cell. Thus, the greater the percentage of land in a cell, the higher the confidence is for snow extent in that cell. Cloud obstruction reduces the confidence index.

The Eight Day CMG Cloud Obscured field indicates how much of the land surface in the cell is persistently obscured during the eight-day period. Cloud percentage in each cell of the Day CMG Cloud Obscured field is calculated in the same way as the percentage of snow, except that the count of cloud observations is used. Data from the Day CMG Snow Cover and Day CMG Cloud Obscured fields can be used together to better understand the observed snow. For example, if MODIS views a snow-covered region and no clouds obstruct the view on that day, then percentage of snow cover is 100 percent. If there is 30 percent cloud cover for that day, the percentage of snow cover is 70 percent.

$$\text{percent cloud obscured} = 100 * \text{count of cloud observations} / \text{count of land}$$

The Snow Spatial QA field provides additional information on algorithm results for each pixel within a spatial context, and it is used as a measure of usefulness for snow-cover data. The QA

information tells if algorithm results were nominal, abnormal, or if other defined conditions were encountered for a pixel.

### 1.1.1 External Metadata File

A separate ASCII text file containing metadata with a .xml file extension accompanies the HDF-EOS file. The metadata file contains some of the same metadata as in the product file, but also includes other information regarding archiving, user support, and post-production QA relative to the granule ordered. The post-production QA metadata may or may not be present depending on whether or not the data granule was investigated for quality assessment. The metadata file should be examined to determine if post-production QA was applied to the granule.

## 1.2 File Naming Convention

---

The file naming convention common to all MODIS products is  
 MOD10C2.A2004057.005.2006260032944.hdf

Refer to Table 1 for an explanation of the variables used in the MODIS file naming convention.

Table 1. Variable Explanation for MODIS File Naming Convention

Variable	Explanation
MOD	MODIS/Terra
10C2	Type of product
A	Acquisition date
2004	Year of data acquisition
057	Day of year of data acquisition (day 57)
005	Version number
2006	Year of production (2006)
260	Day of year of production (day 260)
032944	Hour/minute/second of production in GMT (09:11:04)
hdf	HDF-EOS data format

## 1.3 File Size

---

Data files are typically between 5 - 6 MB using HDF compression.



New in V005, MODIS data files now use HDF data compression. The extent to which compression reduces the file size varies from image to image, but generally it is a factor of 10 or more.

## 1.4 Spatial Coverage

---

Coverage is global; however, snow cover is calculated for only tiles that include land. A  $\pm 55$  degree scanning pattern at 705 km altitude achieves a 2330 km swath with global coverage every one to two days. The following resources can help you select and work with MYD10C2 tiles:

- [MODIS MODLAND Tile Calculator](#)
- [HDF-EOS to GeoTIFF Conversion Tool \(HEG\)](#)

### Latitude Crossing Times

The local equatorial crossing time of the Terra satellite is approximately 10:30 A.M. in a descending node with a sun-synchronous, near-polar, circular orbit.

### 1.4.1 Spatial Resolution

Gridded resolution is 0.05 degrees.

### 1.4.2 Projection

This data set is in a 0.05 degree CMG.

### 1.4.3 Grid

The CMG products contain global snow cover arrays of 7200 columns by 3600 rows. Each cell is 0.05 degree resolution. For more information about the CMG, see the [MODIS Land | MODIS Grids](#) Web page.

## 1.5 Temporal Coverage

---

MODIS data extends from 04 July 2002 to 26 December 2016..

Over the course of the Terra mission, there have been a number of anomalies that have resulted in dropouts in the data. If you are looking for data for a particular date or time and can not find it, please visit the [MODIS/Terra Data Outages](#) Web page.

### 1.5.1 Temporal Resolution

Temporal resolution is 8 days. Eight-day periods begin on the first day of the year and extend into the next year. In some cases, there may not be eight days of input. The data file name indicates the first day in the eight-day period.

Table 3 lists the days covered by each compositing period:

Table 2. Eight-day Compositing Periods

Period	Days	Period	Days	Period	Days	Period	Days
1	1-8	13	97-104	25	193-200	37	289-296
2	9-16	14	105-112	26	201-208	38	297-304
3	17-24	15	113-120	27	209-216	39	305-312
4	25-32	16	121-128	28	217-224	40	313-320
5	33-40	17	129-136	29	225-232	41	321-328
6	41-48	18	137-144	30	233-240	42	329-336
7	49-56	19	145-152	31	241-248	43	337-344
8	57-64	20	153-160	32	249-256	44	345-352
9	65-72	21	161-168	33	257-264	45	353-360
10	73-80	22	169-176	34	265-272	46	361-368 <sup>1</sup>
11	81-88	23	177-184	35	273-280	—	—
12	89-96	24	185-192	36	281-288	—	—

<sup>1</sup>Includes 2 or 3 days from the next year.

## 1.6 Parameter or Variable

---

### 1.6.1 Parameter Description

The snow mapping algorithm for CMG products classifies pixels as snow, snow-free land, cloud, night, masked (Antarctica), or no data. Snow extent is the primary variable of interest in this data set.

### 1.6.2 Parameter Range

Refer to the [MOD10C2 and MYD10C2 Global and Local Snow Cover Attributes, Version 5](#) document for a key to the meaning of the coded integer values in the Maximum Snow Extent Field.

## 2 SOFTWARE AND TOOLS

### 2.1 Data Access Aids

---

The following sites can help you select appropriate MODIS data for your study:

- [MODIS Rapid Response System](#)
- [NASA Goddard Space Flight Center: MODIS Data](#)



- [Space Science and Engineering Center \(SSEC\): Aqua Orbit Tracks GLOBAL Web site](#)

## 2.2 Data Analysis Tools

---

- [Land Processes Distributive Active Archive Center: MODIS Swath Reprojection Tool Distribution Page](#): Software tools that read HDF-EOS files containing MODIS swath data and produce native binary HDF-EOS Grid or GeoTIFF files of gridded data in different map projections.
- [HEG HDF-EOS to GeoTIFF Conversion Tool](#): This free tool converts many types of HDF-EOS data to GeoTIFF, native binary, or HDF-EOS grid format. It also has reprojection, resampling, subsetting, stitching (mosaicing), and metadata preservation and creation capabilities.
- [NCSA HDFView](#): The HDFView is a visual tool for browsing and editing the National Center for Supercomputing Applications (NCSA) HDF4 and HDF5 files. Using HDFView, you can view a file hierarchy in a tree structure, create a new file, add or delete groups and datasets, view and modify the content of a dataset, add, delete, and modify attributes, and replace I/O and GUI components such as table view, image view, and metadata view.
- [Hierarchical Data Format - Earth Observing System \(HDF-EOS\)](#): NSIDC provides more information about the HDF-EOS format, tools for extracting binary and ASCII objects from HDF, information about the hrepack tool for uncompressing HDF-EOS data files, and a list of other HDF-EOS resources.
- [The MODIS Conversion Toolkit \(MCTK\)](#): A free plugin for ENVI that can ingest, process, and georeference every known MODIS data product using either a graphical widget interface or a batch programmatic interface. This includes MODIS products distributed with EASE-Grid projections.

## 3 DATA ACQUISITION AND PROCESSING

### 3.1 Theory of Measurements

---

For information regarding the theory for snow mapping and fractional snow cover, please see the Theory of Measurements section in the MODIS/Terra Snow Cover 5-Min L2 Swath 500m, Version 5 guide document (MOD10\_L2).

### 3.2 Data Acquisition Methods

---

#### 3.2.1 Source or Platform Mission Objectives

MODIS is a key instrument aboard the Terra satellite, a core component of NASA's Earth Observing System (EOS). The EOS includes a series of satellites, a data system, and the world-wide community of scientists supporting a coordinated series of polar-orbiting and low inclination satellites for long-term global observations of the land surface, biosphere, solid Earth, atmosphere, and oceans that together enable an improved understanding of the Earth as an integrated system.

MODIS is playing a vital role in the development of validated, global, and interactive Earth system models able to predict global change accurately enough to assist policy makers in making sound decisions concerning the protection of our environment.

### 3.2.2 MODIS Snow and Sea Ice Global Mapping Project Objectives

Within this overall context, the objectives of the MODIS snow and ice team are to develop and implement algorithms that map snow and ice on a daily basis, and provide statistics of the extent and persistence of snow and ice over eight-day periods. Data at 500 m resolution enables sub-pixel snow mapping for use in regional and global climate models. A study of sub grid-scale snow-cover variability is expected to improve features of a model that simulates Earth radiation balance and land-surface hydrology.

### 3.2.3 Data Collection System

The MODIS sensor contains a system whereby visible light from the earth passes through a scan aperture and into a scan cavity to a scan mirror. The double-sided scan mirror reflects incoming light onto an internal telescope, which in turn focuses the light onto four different detector assemblies. Before the light reaches the detector assemblies, it passes through beam splitters and spectral filters that divide the light into four broad wavelength ranges. Each time a photon strikes a detector assembly, an electron is created. Electrons are collected in a capacitor where they are eventually transferred into the preamplifier. Electrons are converted from an analog signal to digital data, and downlinked to ground receiving stations.

### 3.2.4 Data Acquisition and Processing

The EOS Ground System (EGS) consists of facilities, networks, and systems that archive, process, and distribute EOS and other NASA earth science data to the science and user community. For example, ground stations provide space to ground communication. The EOS Data and Operations System (EDOS) processes telemetry from EOS spacecraft and instruments to generate Level-0 products, and maintains a backup archive of Level-0 products. The MODIS Adaptive Processing System ([MODAPS](#)) is currently responsible for generation of Level-1A data from Level-0 instrument packet data. These data are then used to generate higher level MODIS data products. MODIS snow and ice products are archived at the NSIDC Distributed Active Archive Center (DAAC) and distributed to EOS investigators and other users via external networks and interfaces. Data are available to the public through a variety of interfaces.

## 3.3 Derivation Techniques and Algorithms

---

The MODIS science team is responsible for algorithm development. The MODAPS is responsible for product generation and transfer of products to NSIDC.

A snow-mapping algorithm generates global daily and eight-day snow cover products from MODIS data. The algorithm identifies the presence of snow by reflectance properties in each 500 m pixel for each orbit. The snow mapping algorithm is based on the Normalized Difference Snow Index (NDSI). The NDSI is a ratio of the difference between the infrared reflectance of snow in visible and infrared wavelengths. The NDSI is adaptable for a number of illumination conditions, it does not depend on reflectance for a specific band, and it is partially normalized for atmospheric effects. The algorithm uses MODIS bands 4 (0.55  $\mu\text{m}$ ) and 6 (1.6  $\mu\text{m}$ ) from the Level 1B MOD02HKM product to calculate the NDSI (Hall et al. 1998).

$$\text{NDSI} = (\text{Band 4} - \text{Band 6}) / (\text{Band 4} + \text{Band 6})$$

The [MODIS/Terra Calibrated Radiances 5-Min L1B Swath 500m \(MOD02HKM\)](#) guide document provides the source data that was used to calculate reflectance.

### 3.3.1 Processing Steps

In the MYD10C2 product, the snow cover algorithm maps MYD10A2 eight-day snow cover data at 500 m resolution into the corresponding cell of a 0.05 degree CMG and computes snow and cloud percentages, QA, and a confidence index based on the mapping results. The MODIS Instrument Science Team employed the University of Maryland's [1 km Global Land Cover product](#) to compute the percentage of land in each CMG cell and determine an appropriate classification. CMG cells with at least 12 percent land were classified as land. The global land cover mask was also used in the calculation of the confidence index.

Because Antarctica's surface is typically less than one percent snow-free (a value less than the global error rate for MODIS snow mapping), the algorithm classifies Antarctica as completely snow-covered. This also reduces confusion with cloud signatures.

### 3.3.2 Error Sources

As with any upper level product, the characteristics of and/or anomalies in input data may carry through to the output data product. The following product is input to the algorithms used to create the MYD10C2 product:

- [MYD10A2 - MODIS/Aqua Snow Cover 8-Day L3 Global 500m, Version 5](#)

## 3.4 Quality Assessment

---

Quality indicators for MODIS snow data can be found in the following places:

- AutomaticQualityFlag and the ScienceQualityFlag metadata objects and their corresponding explanations: AutomaticQualityFlagExplanation and ScienceQualityFlagExplanation located in the CoreMetadata.0 global attributes
- Custom local attributes associated with each Scientific Data Set, for example, Snow Cover
- Snow Spatial QA field.

These quality indicators are generated during production or in post-production scientific and quality checks of the data product. For more information on local and global attributes, go to one of the following documents:

- [MOD10C2 and MYD10C2 Global and Local Snow Cover Attributes, Version 5](#)

The AutomaticQualityFlag is automatically set according to conditions for meeting data criteria in the snow mapping algorithm. In most cases, the flag is set to either Passed or Suspect, and in rare instances it may be set to Failed. Suspect means that a significant percentage of the data were anomalous and that further analysis should be done to determine the source of anomalies. The AutomaticQualityFlagExplanation contains a brief message explaining the reason for the setting of the AutomaticQualityFlag. The ScienceQualityFlag and the ScienceQualityFlagExplanation are set after production, either after an automated QA program is run or after the data product is inspected by a qualified snow scientist. Content and explanation of this flag are dynamic so it should always be examined if present.

The [NASA Goddard Space Flight Center: MODIS Land Quality Assessment](#) Web site provides updated quality information for each product.

## 3.5 Sensor or Instrument Description

---

### 3.5.1 Principles of Operation

The MODIS instrument provides 12-bit radiometric sensitivity in 36 spectral bands, ranging in wavelength from 0.4  $\mu\text{m}$  to 14.4  $\mu\text{m}$ . Two bands are imaged at a nominal resolution of 250 m at nadir, five bands at 500 m, and the remaining bands at 1000 m. A  $\pm 55$  degree scanning pattern at a 705 km altitude achieves a 2330 km swath with global coverage every one to two days.

The scan mirror assembly uses a continuously rotating double-sided scan mirror to scan  $\pm 55$  degrees, driven by a motor encoder built to operate 100 percent of the time throughout the six year instrument design life. The optical system consists of a two-mirror off-axis afocal telescope which

directs energy to four refractive objective assemblies: one each for the visible, near-infrared, short wave-infrared, and long wave-infrared spectral regions.

### 3.5.2 Technical Specifications

Table 3. Technical Specifications

<b>Orbit</b>	705 km, 1:30 p.m. descending node (Terra), sun-synchronous, near-polar, circular
<b>Scan Rate</b>	20.3 rpm, cross track
<b>Swath Dimensions</b>	2330 km (cross track) by 10 km (along track at nadir)
<b>Telescope</b>	17.78 cm diameter off-axis, afocal (collimated) with intermediate field stop
<b>Size</b>	1.0 x 1.6 x 1.0 m
<b>Weight</b>	228.7 kg
<b>Power</b>	162.5 W (single orbit average)
<b>Data Rate</b>	10.6 Mbps (peak daytime); 6.1 Mbps (orbital average)
<b>Quantization</b>	12 bits
<b>Spatial Resolution</b>	250 m (bands 1-2) 500 m (bands 3-7) 1000 m (bands 8-36)
<b>Design Life</b>	Six years

### 3.5.3 Spectral Bands

For information on the 36 spectral bands provided by the MODIS instrument, see the [MODIS Spectral Bands Table](#).

### 3.5.4 Sensor or Instrument Measurement Geometry

The MODIS scan mirror assembly uses a continuously rotating double-sided scan mirror to scan  $\pm 55$  degree, with a 20.3 rpm. The viewing swath is 10 km along track at nadir, and 2330 km cross track at  $\pm 55$  degree.

### 3.5.5 Manufacturer of Sensor or Instrument

MODIS instruments were built to NASA specifications by Santa Barbara Remote Sensing, a division of Raytheon Electronics Systems.

### 3.5.6 Calibration

MODIS has a series of on-board calibrators that provide radiometric, spectral, and spatial calibration of the MODIS instrument. The blackbody calibrator is the primary calibration source for thermal bands between 3.5  $\mu\text{m}$  and 14.4  $\mu\text{m}$ , while the Solar Diffuser (SD) provides a diffuse, solar-illuminated calibration source for visible, near-infrared, and shortwave infrared bands. The Solar Diffuser Stability Monitor (SDSM) tracks changes in the reflectance of the SD with reference to the sun so that potential instrument changes are not incorrectly attributed to changes in this calibration source. The Spectroradiometric Calibration Assembly (SRCA) provides additional spectral, radiometric, and spatial calibration.

MODIS uses the moon as an additional calibration technique and for tracking degradation of the SD, by referencing the illumination of the moon since the moon's brightness is approximately the same as that of the Earth. Finally, MODIS deep space views provide a photon input signal of zero, which is used as a point of reference for calibration.

## 4 REFERENCES AND RELATED PUBLICATIONS

Diner, D. J., J. V. Martonchik, C. Borel, S. A. W. Gerstl, H. R. Gordon, Y. Knyazikhin, R. Myneni, B. Pinty, and M. M. Verstraete. 1999. *MISR Level-2 Surface Retrieval Algorithm Theoretical Basis Document*. Pasadena, CA: Jet Propulsion Laboratory.

Earth Science Data and Information System (ESDIS). 1996. *EOS Ground System (EGS) Systems and Operations Concept*. Greenbelt, MD: Goddard Space Flight Center.

Greuell, W. and J. Oerlemans. (2005). Validation of AVHRR- and MODIS-Derived Albedos of Snow and Ice Surfaces by Means of Helicopter Measurements. *Journal of Glaciology*, 51(172):37-48.

Hall, Dorothy K., George A. Riggs, and Vincent V. Salomonson. September 2001a. *Algorithm Theoretical Basis Document (ATBD) for the MODIS Snow-, Lake Ice- and Sea Ice-Mapping Algorithms*. Greenbelt, MD: Goddard Space Flight Center. <<http://modis-snow-ice.gsfc.nasa.gov/atbd.html>> .

Hall, Dorothy K. and J. Martinec. 1985. *Remote Sensing of Ice and Snow*. London: Chapman and Hall.

Hall, Dorothy K., J. L. Foster, D. L. Verbyla, A. G. Klein, and C. S. Benson. 1998. Assessment of Snow Cover Mapping Accuracy in a Variety of Vegetation Cover Densities in Central Alaska. *Remote Sensing of the Environment* 66:129-137.

Hall, Dorothy K., J. L. Foster, Vincent V. Salomonson, A. G. Klein, and J. Y. L. Chien. 2001b. Development of a Technique to Assess Snow-Cover Mapping Accuracy from Space. *IEEE Transactions on Geoscience and Remote Sensing* 39(2):232-238.

Hall, Dorothy K. and George A. Riggs. 2006. Assessment of Errors in the MODIS Suite of Snow-Cover Products. *Hydrological Processes*, in press.

Hapke, B. 1993. *Theory of Reflectance and Emittance Spectroscopy*. Cambridge: Cambridge University Press.

Justice, C. O. 2002. An Overview of MODIS Land Data Processing and Product Status. *Remote Sensing of the Environment*, 83(1):3-15.

Klein, A. *MODIS Snow Albedo Prototype*. 2003. <[http://geog.tamu.edu/klein/modis\\_albedo/](http://geog.tamu.edu/klein/modis_albedo/)> Accessed October 2006.

Klein, A. G. and Julienne Stroeve. 2002. Development and Validation of a Snow Albedo Algorithm for the MODIS Instrument. *Annals of Glaciology* 34:45-52.

Klein, A. G., Dorothy K. Hall, and George A. Riggs. 1998. Improving Snow-Cover Mapping in Forests Through the use of a Canopy Reflectance Model. *Hydrologic Processes* 12(10-11):1723-1744.

Markham, B. L. and J. L. Barker. 1986. Landsat MSS and TM Post-Calibration Dynamic Ranges, Exoatmospheric Reflectances and At-Satellite Temperatures. *EOSAT Technical Notes* 1:3-8.

MODIS Characterization and Support Team (MCST). 2000. *MODIS Level-1B Product User's Guide for Level-1B Version 2.3.x Release 2*. MCST Document #MCM-PUG-01-U-DNCN.

MODIS Science and Instrument Team. *MODIS Web*. July 2003. <<http://modis.gsfc.nasa.gov/>> Accessed October 2000.

Painter, Thomas H. and J. Dozier. 2004. Measurements of the Hemispherical Directional Reflectance of Snow at Fine Spectral and Angular Resolution. *Journal of Geophysical Research-Atmospheres*, 109(D18):D18115. doi:10.1029/2003JD004458.

Pearson II, F. 1990. *Map Projections: Theory and Applications*. Boca Raton, FL: CRC Press, Inc.

Riggs, George A., Dorothy K. Hall, and Vincent V. Salomonson. December 2006. *MODIS Snow Products User Guide to Collection 5*. [PDF](#).

Stroeve, Julienne, Anne Nolin, and K. Steffen. 1997. Comparison of AVHRR-Derived and In Situ Surface Albedo Over the Greenland Ice Sheet. *Remote Sensing of the Environment*, 62:262-276.

Stroeve, Julienne, J. E. Box, Terry Haran. 2006. Evaluation of the MODIS (MOD10A1) Daily Snow Albedo Product Over the Greenland Ice Sheet. *Remote Sensing of the Environment*, 105:155-171.

United States Geological Survey. "Sinusoidal Equal Area." *Map Projections*. 2003.  
<<http://erg.usgs.gov/isb/pubs/MapProjections/projections.html#sinusoidal>> Accessed December 2000.

Wiscombe, W. J. and S. G. Warren. 1980. A Model for the Spectral Albedo of Snow I: Pure Snow. *Journal of the Atmospheric Sciences* 37:2712-2733.

## 4.1 Related Data Collections

---

See [MODIS Data | Data Sets](#) for a complete list of MODIS snow and sea ice products available from NSIDC.

# 5 CONTACTS AND ACKNOWLEDGMENTS

## 5.1 Principle Investigators

---

### **Dorothy K. Hall**

National Aeronautics and Space Administration (NASA) Goddard Space Flight Center (GSFC)  
Mail stop 614.1  
Greenbelt, MD 20771

### **Vincent V. Salomonson**

Room 809 WBB  
Department of Meteorology  
University of Utah  
Salt Lake City, UT 84112

### **George A. Riggs**

NASA GSFC  
Science Systems and Applications, Inc.  
Mail stop 614.1  
Greenbelt, MD 20771



## 6 DOCUMENT INFORMATION

### 6.1 Publication Date

---

February 2004

### 6.2 Date Last Updated

---

September 2023