



MODIS/Aqua Sea Ice Extent Daily L3 Global 1km EASE-Grid Day, Version 5

USER GUIDE

How to Cite These Data

As a condition of using these data, you must include a citation:

Hall, D. K., V. V. Salomonson, and G. A. Riggs. 2006. *MODIS/Aqua Sea Ice Extent Daily L3 Global 1km EASE-Grid Day, Version 5*. [Indicate subset used]. Boulder, Colorado USA. NASA National Snow and Ice Data Center Distributed Active Archive Center.
<https://doi.org/10.5067/HUYRXHTDMIQU>. [Date Accessed].

FOR QUESTIONS ABOUT THESE DATA, CONTACT NSIDC@NSIDC.ORG

FOR CURRENT INFORMATION, VISIT <https://nsidc.org/data/MYD29P1D>



National Snow and Ice Data Center

TABLE OF CONTENTS

1	DETAILED DATA DESCRIPTION	3
1.1	Format.....	3
1.1.1	Description of Data Fields.....	3
1.1.2	External Metadata File.....	4
1.2	File Naming Convention.....	4
1.3	File Size	5
1.4	Spatial Coverage.....	5
1.4.1	Latitude Crossing Times.....	5
1.4.2	Spatial Resolution.....	5
1.4.3	Projection and Grid Description	5
1.5	Temporal Coverage	6
1.5.1	Temporal Resolution	7
1.6	Parameter or Variable	7
1.6.1	Parameter Description.....	7
1.6.2	Parameter Range	7
2	SOFTWARE AND TOOLS.....	7
2.1	Data Access Aids.....	7
2.2	Data Analysis Tools	7
3	DATA ACQUISITION AND PROCESSING	8
3.1	Theory of Measurements	8
3.2	Data Acquisition Methods	8
3.2.1	Source or Platform Mission Objectives.....	8
3.2.2	MODIS Snow and Sea Ice Global Mapping Project Objectives	9
3.2.3	Data Collection System	9
3.2.4	Data Acquisition and Processing.....	9
3.3	Derivation Techniques and Algorithms.....	9
3.3.1	Processing Steps.....	10
3.3.2	Error Sources	10
3.4	Quality Assessment	10
3.5	Sensor or Instrument Description.....	11
3.5.1	Calibration	12
4	REFERENCES AND RELATED PUBLICATIONS	13
4.1	References.....	13
4.2	Related Data Collections.....	14
4.3	Related Websites	14
5	CONTACTS AND ACKNOWLEDGMENTS.....	15
5.1	Principal Investigators	15
5.2	Support Investigator	15
6	DOCUMENT INFORMATION.....	15

6.1	Publication Date	15
6.2	Date Last Updated	15

1 DETAILED DATA DESCRIPTION

The MODIS science team continually seeks to improve the algorithms used to generate MODIS data sets. Whenever new algorithms become available, the [MODIS Adaptive Processing System \(MODAPS\)](#) reprocesses the entire MODIS collection—atmosphere, land, cryosphere, and ocean data sets—and a new version is released. NSIDC strongly encourages users to work with the most recent version.

Consult the following resources for more information about MODIS Version 5 data, including known problems, production schedules, and future plans:

- [MODIS Sea Ice Products User Guide to Collection 5](#)
- [The MODIS Snow and Sea Ice Global Mapping Project](#)
- [NASA Goddard Space Flight Center | MODIS Land Quality Assessment](#)
- [MODIS Land Team Validation | Status for Snow Cover/Sea Ice \(MOD10/29\)](#)

This data set is retired and no longer available for download. The most up-to-date version of this data can be accessed on the NSIDC website [here](#).

1.1 Format

MODIS sea ice products are archived in compressed HDF-EOS format, which employs point, swath, and grid structures to geolocate the data fill fields to geographic coordinates. This data compression should be transparent to most users since HDF capable software tools automatically uncompress the data. See the [Hierarchical Data Format - Earth Observing System \(HDF-EOS\)](#) website for more information about the HDF-EOS data format.

Data can also be obtained in GeoTIFF format from [Reverb | ECHO](#), NASA's Next Generation Earth Science Discovery Tool.

MOD29P1D/MYD29P1D data sets consist of 951 x 951 cells of tiled data in the Lambert Azimuth Equal Area Projection. Each data granule contains HDF-EOS local attribute fields, which are stored with their associated Scientific Data Set (SDS). Each data granule also contains metadata either stored as global attributes or as HDF-predefined fields, which are stored with each Scientific Data Set (SDS). This information can be found in the [MOD29P1D and MYD29P1D Version 5 Local and Global Sea Ice Attributes](#) document.

1.1.1 Description of Data Fields

- **Sea Ice by Reflectance** - the sea ice algorithm identifies pixels as being sea ice, open ocean, cloud, land, inland water, or other condition. Sea ice is distinguished from open water based on reflective properties.

- Ice Surface Temperature (IST) - IST data are expressed in kelvins and are stored as scaled integer data in HDF-EOS calibrated form. You must convert data to kelvins using the calibration data as given in the HDF predefined local attributes:
 $IST = scale_factor * (data\ value - add_offset)$

Where:

scale_factor = 0.01

data value = ice surface temperature

add_offset = 0

The valid range for IST is 210.00 to 313.00 K

- Sea Ice by Reflectance Spatial QA and Ice Surface Temperature Spatial QA - these fields store the quality of the retrieval on a pixel-by-pixel basis. QA information tells if the algorithm results were good quality, other quality, or if other defined conditions were encountered for a pixel. For example, if all the input data and calculations in the algorithm were nominal for a pixel, the QA field is set to good quality. If data showed abnormal values for a pixel, such as out of range, the QA field is set to other quality. See the [MOD29P1D and MYD29P1D Version 5 Local and Global Sea Ice Attributes](#) document for all the possible QA flag sample values in sea ice products.

1.1.2 External Metadata File

A separate ASCII text file containing metadata with a .xml file extension accompanies the HDF-EOS file. The metadata file contains some of the same metadata as in the product file, but also includes other information regarding archiving, user support, and post production QA relative to the granule ordered. The post-production QA metadata may or may not be present depending on whether or not the data granule has been investigated for quality assurance. The metadata file should be examined to determine if post-production QA has been applied to the granule.

1.2 File Naming Convention

The file naming convention used for this data set is

MOD29P1D.A2000057.h04v06.005.2006252042343.hdf. Refer to Table 1 for an explanation of the variables used in the MODIS file naming convention.

Table 1. Variable Explanation for MODIS File Naming Convention

Variable	Explanation
MOD	MODIS/Terra
MYD	MODIS/Aqua
29P1D	Type of product
A	Acquisition date
2000	Year of data acquisition
057	Day of year of data acquisition (day 57)

Variable	Explanation
h04v06	Horizontal tile number and vertical tile number. For further information, see Section 1.4.3.2 Grid.
005	Version number
2006	Year of production (2006)
252	Day of year of production (day 252)
042343	Hour/minute/second of production in GMT (04:23:43)
hdf	HDF-EOS data format

1.3 File Size

Data files are typically between 0.5 - 1.5 MB using HDF compression.

Note: New in V005, data files now use HDF data compression. The extent to which compression reduces the file size varies from image to image, but generally it is a factor of 10 or more.

1.4 Spatial Coverage

Coverage is global; however, only ocean pixels are run through the sea ice algorithm.

1.4.1 Latitude Crossing Times

The local equatorial crossing time of the Terra (Aqua) satellite is approximately 10:30 a.m. (1:30 p.m.), in a descending (ascending) node with a sun-synchronous, near-polar, circular orbit.

1.4.2 Spatial Resolution

Gridded resolution is 1 km.

1.4.3 Projection and Grid Description

1.4.3.1 Projection

MOD29P1D/MYD29P1D data sets utilize polar tile grids based on the Lambert Azimuthal Equal-Area projection. Meridians are straight lines that intersect at the poles while lines of latitude are circles with their centers at either pole. The following table lists some of the key parameters for this projection:

Table 2. Lambert Azimuthal Equal Area Map Projection Parameters

Parameter	Value
Earth radius	6371228.0 meters
Projection origin	North: 90° lat, 0° lon South: -90° lat, 0° lon
Orientation	North: 0° lon, oriented vertically at bottom South: 0° lon, oriented vertically at top
Upper left corner (m)	-9058902.1845(x) 9058902.1845(y)
Lower right corner (m)	9058902.1845(x) -9058902.1845(y)
Scale (m)	1002.7010(x) 1002.7010(y)

1.4.3.2 Grid

MOD29P1D/MYD29P1D data files are provided as tiles of data gridded in the original EASE-Grid Lambert Azimuthal Equal Area map projection. Tiles contain 951 x 951 cells. The global tile grid is partitioned into separate Northern and Southern Hemisphere polar grids, with half of the tiles (313) in the north and half in the south. The coordinate system, designated by (horizontal, vertical) ordered pairs, starts with (h00,v00) in the upper left corner of the northern grid and proceeds rightward (horizontal) and downward (vertical) to tile (h18, v18) in the bottom right. The southern grid begins where the northern grid ends, with tile (h00,v20) in the upper left and tile (v18,h38) in the lower right.

Additional information about this grid is available on the following web pages, including bounding coordinates for each tile, maps that show tile locations for the Northern and Southern Hemisphere grids, and the MODLAND Tile Calculator tool, which can convert between MODIS tile numbers and latitude/longitude:

- [EASE-Grid Tile Locations and Bounding Coordinates for MODIS Sea Ice Products](#)
- [MODIS MODLAND Tile Calculator](#)

For descriptions of all the projections and grids used for MODIS data sets, see the MODIS Land team's [MODIS Grids](#) web page. A complete description of EASE-Grid is available at [EASE-Grid Data | Overview](#).

1.5 Temporal Coverage

MODIS Terra data extend from 24 February, 2000 to present.

MODIS Aqua data extend from 4 July, 2002 to present.

Over the course of the Terra and Aqua missions, a number of anomalies have resulted in data gaps. If you are looking for data for a particular date or time and cannot find it, please visit the [MODIS/Terra Data Outages](#) and [MODIS/Aqua Data Outages](#) web pages.

1.5.1 Temporal Resolution

Daily

1.6 Parameter or Variable

1.6.1 Parameter Description

The sea ice algorithm classifies pixels as sea ice, cloud, open ocean, inland water, or land. In the Sea Ice by Reflectance field, sea ice is distinguished from open water based on reflective properties. In the IST field, pixels classified as sea ice contain an IST value in kelvins, and pixel values are scaled by 100 for all classes. The IST algorithm was designed for sea ice; however, IST values are provided for areas over open ocean.

1.6.2 Parameter Range

Refer to the [MOD29P1D and MYD29P1D Version 5 Local and Global Sea Ice Attributes](#) document for a key to the meaning of the coded integer values in the Sea Ice by Reflectance Field and Ice Surface Temperature Field.

2 SOFTWARE AND TOOLS

2.1 Data Access Aids

The following sites can help you select appropriate MODIS data for your study:

- [MODIS Rapid Response System](#)
- [NASA Goddard Space Flight Center: MODIS Land Global Browse Images](#)

2.2 Data Analysis Tools

The following software tools can help you analyze the data:

- [Land Processes Distributive Active Archive Center: MODIS Swath Reprojection Tool Distribution Page](#): Software tools that read HDF-EOS files containing MODIS swath data and produce native binary HDF-EOS Grid or GeoTIFF files of gridded data in different map projections.

- [HEG HDF-EOS to GeoTIFF Conversion Tool](#): This free tool converts many types of HDF-EOS data to GeoTIFF, native binary, or HDF-EOS grid format. It also has reprojection, resampling, subsetting, stitching (mosaicing), and metadata preservation and creation capabilities.
- [NCSA HDFView](#): The HDFView is a visual tool for browsing and editing the National Center for Supercomputing Applications (NCSA) HDF4 and HDF5 files. Using HDFView, you can view a file hierarchy in a tree structure, create a new file, add or delete groups and datasets, view and modify the content of a dataset, add, delete, and modify attributes, and replace I/O and GUI components such as table view, image view, and metadata view.
- [Hierarchical Data Format - Earth Observing System \(HDF-EOS\)](#): NSIDC provides more information about the HDF-EOS format, tools for extracting binary and ASCII objects from HDF, information about the hrepack tool for uncompressing HDF-EOS data files, and a list of other HDF-EOS resources.
- [The MODIS Conversion Toolkit \(MCTK\)](#): A free plugin for ENVI that can ingest, process, and georeference every known MODIS data product using either a graphical widget interface or a batch programmatic interface. This includes MODIS products distributed with EASE-Grid projections.

3 DATA ACQUISITION AND PROCESSING

3.1 Theory of Measurements

For information regarding the theory for sea ice mapping and ice surface temperature retrieval, please see the Theory of Measurements section in the [MODIS/Aqua Sea Ice Extent 5-Min L2 Swath 1km \(MYD29\), Version 5](#) user guide.

3.2 Data Acquisition Methods

3.2.1 Source or Platform Mission Objectives

MODIS is a key instrument aboard Terra and Aqua, the flagship satellites of NASA's Earth Observing System (EOS). The EOS includes a series of satellites, a data system, and the worldwide community of scientists supporting a coordinated series of polar-orbiting and low inclination satellites for long-term global observations of the land surface, biosphere, solid Earth, atmosphere, and oceans that together enable an improved understanding of the Earth as an integrated system. MODIS is playing a vital role in the development of validated, global, and interactive Earth system models able to predict global change accurately enough to assist policy makers in making sound decisions concerning the protection of our environment ([NASA's MODIS website 2006](#), [NASA's Terra website 2006](#), and [NASA's EOS website 2006](#)).

3.2.2 MODIS Snow and Sea Ice Global Mapping Project Objectives

Within this overall context, the objectives of the MODIS snow and ice team are to develop and implement algorithms that map snow and ice on a daily basis, and provide statistics of the extent and persistence of snow and ice over eight-day periods. Data at 500 m resolution enables sub-pixel snow mapping for use in regional and global climate models. A study of sub grid-scale snow-cover variability is expected to improve features of a model that simulates Earth radiation balance and land-surface hydrology (Hall et al., 1998).

3.2.3 Data Collection System

The MODIS sensor contains a system whereby visible light from the earth passes through a scan aperture and into a scan cavity to a scan mirror. The double-sided scan mirror reflects incoming light onto an internal telescope, which in turn focuses the light onto four different detector assemblies. Before the light reaches the detector assemblies, it passes through beam splitters and spectral filters that divide the light into four broad wavelength ranges. Each time a photon strikes a detector assembly, an electron is created. Electrons are collected in a capacitor where they are eventually transferred into the preamplifier. Electrons are converted from an analog signal to digital data, and down linked to ground receiving stations.

3.2.4 Data Acquisition and Processing

The EOS Ground System (EGS) consists of facilities, networks, and systems that archive, process, and distribute EOS and other NASA earth science data to the science and user community. For example, ground stations provide space to ground communication. The EOS Data and Operations System (EDOS) processes telemetry from EOS spacecraft and instruments to generate Level-0 products, and maintains a backup archive of Level-0 products. The [NASA Goddard Space Flight Center: MODIS Adaptive Processing System \(MODAPS\) Services](#) is currently responsible for generation of Level-1A data from Level-0 instrument packet data. These data are then used to generate higher level MODIS data products, including MOD10_L2. MODIS snow and ice products are archived at the NSIDC Distributed Active Archive Center (DAAC) and distributed to EOS investigators and other users via external networks and interfaces. Data are available to the public through a variety of interfaces.

3.3 Derivation Techniques and Algorithms

The MODIS science team is responsible for algorithm development. The MODIS Data Processing System (MODAPS) is responsible for product generation and transfer of products to NSIDC.

3.3.1 Processing Steps

For more information regarding the processing steps used as the input to this data set, please see the Processing Steps section in the [MODIS/Aqua Sea Ice Extent 5-Min L2 Swath 1km \(MYD29\), Version 5](#) user guide.

The sea ice algorithm selects an observation of the day from multiple observations mapped to a MYD29GD grid cell. A scoring algorithm selects the most favorable observation of the day based on the MYD29GD derived solar elevation, observation coverage in a grid cell, and distance from nadir. The objective is to select observations that are near nadir, acquired near noon local time, and have a large coverage area in a grid cell. This algorithm applies to daytime reflectance data. In day mode, MODIS collects both visible and thermal data. The scoring algorithm uses the visible data to determine the observation of the day for reflectance and thermal data. The score for each observation is given by the following formula:

$$\text{score} = (0.5x \text{ solar elevation}) + (0.3x \text{ observation coverage}) + (0.2x \text{ distance from NADIR})$$

The observation with the highest score for a grid cell is selected as the observation for the day. The thermal observation corresponding to the visible observation is the IST observation of the day (Riggs, Hall, and Salomonson, 2006).

3.3.2 Error Sources

As with any upper-level product, the characteristics of or anomalies in input data may carry through to the output data product. The following products are input to MYD29P1D:

- [MYD29PGD - MODIS/Aqua Sea Ice Extent Daily L2G Global 1km EASE-Grid Day](#), which is further described in the [MODIS Sea Ice Products User Guide to Collection 5](#).
- MYDPTPGD - MODIS/Aqua Observation Pointers Daily L2G Global 1km Polar Grid Day - This product is not retained.
- MYDMGPGD - MODIS/Aqua Geolocation Angles Daily L2G Global 1 km EASE-Grid Day - This product is not retained.

3.4 Quality Assessment

All MODIS/Terra and MODIS/Aqua sea ice products are considered validated or at stage 2 meaning that accuracy has been assessed over a widely distributed set of locations and time periods via several ground-truth and validation campaigns.

Quality indicators for MODIS sea ice data can be found in the following three places:

- AutomaticQualityFlag and the ScienceQualityFlag metadata objects and their corresponding explanations: AutomaticQualityFlagExplanation and ScienceQualityFlagExplanation located in the CoreMetadata.0 global attributes
- Custom local attributes associated with each SDS, for example Ice Surface Temperature
- The Pixel QA SDS that accompanies each data field, for example, Ice Surface Temperature Spatial QA.

These quality indicators are generated during production or in post-production scientific and quality checks of the data product. See the [MOD29P1D and MYD29P1D Version 5 Local and Global Sea Ice Attributes](#) document for more information on local and global attributes.

The ScienceQualityFlag and the ScienceQualityFlagExplanation may be updated after production, either after an automated QA program is run or after the data product is inspected by a qualified scientist. Content and explanation of this flag are dynamic so it should always be examined if present in the external metadata file. A sampling of products will be inspected. Random sampling or support of specific events, such as field campaigns, may also be conducted.

The IST Spatial QA and Sea Ice by Reflectance Spatial QA data fields provide additional information on algorithm results for each pixel within a spatial context, and are used as a measure of usefulness for sea ice data. QA data are stored as coded integer values and tell if algorithm results were nominal, abnormal, or if other defined conditions were encountered for a pixel (Riggs, Hall, and Salomonson, 2006).

The [NASA Goddard Space Flight Center: MODIS Land Quality Assessment](#) website provides updated quality information for each product.

3.5 Sensor or Instrument Description

The MODIS instrument provides 12-bit radiometric sensitivity in 36 spectral bands ranging in wavelength from 0.4 μm to 14.4 μm . Two bands are imaged at a nominal resolution of 250 m at nadir, five bands at 500 m, and the remaining bands at 1000 m. A ± 55 -degree scanning pattern at an altitude of 705 km achieves a 2330 km swath with global coverage every one to two days.

The scan mirror assembly uses a continuously rotating, double-sided scan mirror to scan ± 55 degrees, and is driven by a motor encoder built to operate 100 percent of the time throughout the six-year instrument design life. The optical system consists of a two-mirror, off-axis afocal telescope which directs energy to four refractive objective assemblies, one each for the visible, near-infrared, short- and mid-wavelength infrared, and long wavelength infrared spectral regions.

The MODIS instruments on the Terra and Aqua space vehicles were built to NASA specifications by Santa Barbara Remote Sensing, a division of Raytheon Electronics Systems. Table 3 contains the instruments' technical specifications:

Table 3. MODIS Technical Specifications

Variable	Description
Orbit	705 km altitude, sun-synchronous, near-polar, circular. Equatorial crossing times: Terra: 10:30 A.M., descending node Aqua: 1:30 P.M., ascending node
Scan Rate	20.3 rpm, cross track
Swath Dimensions	2330 km (cross track) by 10 km (along track at nadir)
Telescope	17.78 cm diameter off-axis, afocal (collimated) with intermediate field stop
Size	1.0 m x 1.6 m x 1.0 m
Weight	228.7 kg
Power	162.5 W (single orbit average)
Data Rate	10.6 Mbps (peak daytime); 6.1 Mbps (orbital average)
Quantization	12 bits
Spatial Resolution	250 m (bands 1-2) 500 m (bands 3-7) 1000 m (bands 8-36)
Design Life	6 years

3.5.1 Calibration

MODIS has a series of on-board calibrators that provide radiometric, spectral, and spatial calibration of the MODIS instrument. The blackbody calibrator is the primary calibration source for thermal bands between 3.5 μm and 14.4 μm , while the Solar Diffuser (SD) provides a diffuse, solar-illuminated calibration source for visible, near-infrared, and short-wave infrared bands. The Solar Diffuser Stability Monitor tracks changes in the reflectance of the SD with reference to the sun so that potential instrument changes are not incorrectly attributed to changes in this calibration source. The Spectroradiometric Calibration Assembly provides additional spectral, radiometric, and spatial calibration.

MODIS uses the moon as an additional calibration technique and for tracking degradation of the SD by referencing the illumination of the moon since the moon's brightness is approximately the same as that of the Earth. Finally, MODIS deep space views provide a photon input signal of zero, which is used as a point of reference for calibration.

For additional details about the MODIS instruments, see NASA's [MODIS | About](#) web page.

4 REFERENCES AND RELATED PUBLICATIONS

4.1 References

Earth Science Data and Information System (ESDIS). 1996. *EOS Ground System (EGS) Systems and Operations Concept*. Greenbelt, MD: Goddard Space Flight Center.

Hall, Dorothy K., J. L. Foster, D. L. Verbyla, A. G. Klein, and C. S. Benson. 1998. Assessment of Snow Cover Mapping Accuracy in a Variety of Vegetation Cover Densities in Central Alaska. *Remote Sensing of the Environment* 66:129-137.

Hall, Dorothy K., Jeffrey R. Key, Kimberly A. Casey, George A. Riggs, and Donald Cavalieri. 2004. Sea Ice Surface Temperature Product From MODIS. *IEEE Transactions on Geoscience and Remote Sensing* 42:5.

Hall, Dorothy K. and J. Martinec. 1985. *Remote Sensing of Ice and Snow*. London: Chapman and Hall.

Hall, Dorothy K., George A. Riggs, and Vincent V. Salomonson. 1995. Development of Methods for Mapping Global Snow Cover Using Moderate Resolution Imaging Spectroradiometer (MODIS). *Remote Sensing of the Environment* 54(2):127-140.

Hall, Dorothy K., George A. Riggs, and Vincent V. Salomonson. September 2001. *Algorithm Theoretical Basis Document (ATBD) for the MODIS Snow and Sea Ice-Mapping Algorithms*. Greenbelt, MD: Goddard Space Flight Center. <http://modis-snow-ice.gsfc.nasa.gov/?c=atbd&t=atbd> (accessed March 30, 2015).

Hall, Dorothy K. and George A. Riggs. 2007. Accuracy assessment of the MODIS snow-cover products. *Hydrological Processes* 21(12):1534-1547. doi: <https://doi.org/10.1002/hyp.6715>

Hall, D.K., S.V. Nghiem, I.G. Rigor, and J.A. Miller. 2015. Uncertainties of temperature measurements on snow-covered land and sea ice from in-situ and MODIS data during BROMEX. *Journal of Applied Meteorology and Climatology*. doi: <http://dx.doi.org/10.1175/JAMC-D-14-0175.1>

Hapke, B. 1993. *Theory of Reflectance and Emittance Spectroscopy*. Cambridge: Cambridge University Press.

Key, J. R., J. B. Collins, Chuck Fowler, and R. S. Stone. 1997. High Latitude Surface Temperature Estimates From Thermal Satellite Data. *Remote Sensing of the Environment* 61:302-309.

Key, J. R., J. A. Maslanik, T. Papakyriakou, Mark C. Serreze, and A. J. Schweiger. 1994. On the Validation of Satellite-Derived Sea Ice Surface Temperature. *Arctic* 47:280-287.

Markham, B. L. and J. L. Barker. 1986. Landsat MSS and TM Post-Calibration Dynamic Ranges, Exoatmospheric Reflectances and At-Satellite Temperatures. *EOSAT Technical Notes* 1:3-8.

MODIS Characterization and Support Team (MCST). 2000. *MODIS Level-1B Product User's Guide for Level-1B Version 2.3.x Release 2*. MCST Document #MCM-PUG-01-U-DNCN.

MODIS Science and Instrument Team. *MODIS Web*. July 2003. <<https://modis.gsfc.nasa.gov/>> Accessed October 2000.

Pearson II, F. 1990. *Map Projections: Theory and Applications*. Boca Raton, FL: CRC Press, Inc.

Riggs, George A., Dorothy K. Hall, and S. A. Ackerman. 1999. Sea Ice Extent and Classification Mapping With the Moderate Resolution Imaging Spectroradiometer Airborne Simulator. *Remote Sensing of the Environment* 68:152-163.

Riggs, George A, Dorothy K. Hall, and Steven A. Ackerman. "Sea Ice Extent and Classification Mapping with the Moderate Resolution Imaging Spectroradiometer Airborne Simulator." https://modis-snow-ice.gsfc.nasa.gov/?c=pap_seaice. [accessed 2015]

Scambos, T.A., T.M. Haran, and R. Massom. 2006. Validation of AVHRR and MODIS Ice Surface Temperature Products Using In Situ Radiometers. *Annals of Glaciology*, 44:345-351.

Wiscombe, W. J. and S. G. Warren. 1980. A Model for the Spectral Albedo of Snow I: Pure Snow. *Journal of the Atmospheric Sciences* 37:2712-2733.

4.2 Related Data Collections

See [MODIS | Data Sets](#) for all the MODIS snow cover and sea ice data sets available from NSIDC.

4.3 Related Websites

- [MODIS @ NASA Goddard Space Flight Center](#)
- [The MODIS Snow and Sea Ice Global Mapping Project](#)

5 CONTACTS AND ACKNOWLEDGMENTS

5.1 Principal Investigators

Dorothy K. Hall

NASA Goddard Space Flight Center (GSFC)
Greenbelt, Maryland, USA

Vincent V. Salomonson

University of Utah
Department of Meteorology
Salt Lake City, Utah, USA

5.2 Support Investigator

George A. Riggs

NASA Goddard Space Flight Center (GSFC)
Science Systems and Applications, Inc.
Greenbelt, Maryland, USA

6 DOCUMENT INFORMATION

6.1 Publication Date

February 2004

6.2 Date Last Updated

September 2023