

MEaSUREs Greenland Annual Ice Sheet Velocity Mosaics from SAR and Landsat, Version 3

USER GUIDE

How to Cite These Data

As a condition of using these data, you must include a citation:

Joughin, I. 2017, updated 2021. *MEaSUREs Greenland Annual Ice Sheet Velocity Mosaics from SAR and Landsat,* Version 3. [Indicate subset used]. Boulder, Colorado USA. NASA National Snow and Ice Data Center Distributed Active Archive Center. https://doi.org/10.5067/10.5067/C2GFA20CXUI4. [Date Accessed].

FOR QUESTIONS ABOUT THESE DATA, CONTACT NSIDC@NSIDC.ORG

FOR CURRENT INFORMATION, VISIT https://nsidc.org/data/NSIDC-0725



TABLE OF CONTENTS

DATA	DESCRIPTION	3
1.1 F	Parameters	3
1.1.1	Ice Velocity Parameters	4
1.1.2	Temporal Offset	5
1.1.3	Error Estimates	5
1.1.4	Landsat 8 and Synthetic Aperture Radar Shapefiles	5
1.1.5	Browse Files	6
1.2 F	File Information	6
1.2.1	Format	6
1.2.2	Naming Convention	7
1.2.3	Example File Names	7
1.3	Spatial Information	8
1.3.1	Coverage	8
1.3.2	Resolution	8
1.3.3	Geolocation	9
1.4	Femporal Information	10
1.4.1	Coverage	10
1.4.2	Resolution	10
DATA	ACQUISITION AND PROCESSING	.10
2.1	Acquisition	10
2.2 F	Processing	11
2.3 E	Baseline Fits	11
2.3.1	Aggregation and Weighting	12
2.3.2	Temporal Offset Calculation	12
2.3.3	Potential Artifacts	13
2.3.4	Interpolated Points	13
2.3.5	Areas with No Data	13
2.3.6	Geometric Terrain Correction	13
2.3.7	GDAL-Generated Cloud Optimized GeoTIFFs	14
2.4 (Quality, Errors, and Limitations	14
2.5 I	nstrumentation	15
2.5.1	Description	15
SOFT	WARE AND TOOLS	.15
VERS	SION HISTORY	.16
RELA	TED DATA SETS	.18
RELA	TED WEBSITES	.18
CON	FACTS AND ACKNOWLEDGMENTS	.18
	RENCES	
	1.1 F 1.1.1 1.1.2 1.1.3 1.1.4 1.1.5 1.2 F 1.2.1 1.2.2 1.2.3 1.3 S 1.3.1 1.3.2 1.3.3 1.4 T 1.4.1 1.4.2 DATA 2.2 F 2.3 E 2.3.1 2.3.2 2.3.3 2.3.4 2.3.5 2.3.6 2.3.7 2.4 (2.2 2.5 I SOFT VERS RELA RELA	1.1.1 Ice Velocity Parameters 1.1.2 Temporal Offset 1.1.3 Error Estimates 1.1.4 Landsat 8 and Synthetic Aperture Radar Shapefiles 1.1.5 Browse Files 1.2 File Information 1.2.1 Format 1.2.2 Naming Convention 1.2.3 Example File Names 1.3 Spatial Information 1.3.1 Coverage 1.3.2 Resolution 1.3.3 Geolocation 1.4 Temporal Information 1.4.1 Coverage 1.4.2 Resolution DATA ACQUISITION AND PROCESSING 2.1 Acquisition 2.2 Processing 2.3 Baseline Fits 2.3.1 Aggregation and Weighting 2.3.2 Temporal Offset Calculation 2.3.3 Potential Artifacts 2.3.4 Interpolated Points 2.3.5 Areas with No Data 2.3.6 Geometric Terrain Correction 2.3.7 GDAL-Generated Cloud Optimized GeoTIFFs 2.4 Quality, Errors, and

9	DOC	CUMENT INFORMATION	19
	9.1	Publication Date	.19
	9.2	Date Last Updated	.19

1 DATA DESCRIPTION

These data provide annual surface velocity estimates for the Greenland Ice Sheet and periphery. To access quarterly or monthly velocities see related GIMP data sets: *MEaSUREs Greenland Quarterly Ice Sheet Velocity Mosaics from SAR and Landsat and MEaSUREs Greenland Monthly Ice Sheet Velocity Mosaics from SAR and Landsat.* Refer to the Version History table for details about changes to the data set.




Figure 1. Sample browse.jpg file for the dates 01 December 18 to 30 November 2019

1.1 Parameters

The overall parameter for this data set is ice velocity.

1.1.1 Ice Velocity Parameters



Figure 2. Sample vx.tif file for the dates 01 December 18 to 30 November 2019



Figure 3.Sample vy.tif file for the dates 01 December 18 to 30 November 2019.



Figure 4. Sample vv.tif file for the dates 01 December 18 to 30 November 2019; gray scale version of color log scale velocity saturating at 3000 m/year.



Figure 5. Sample dT.tif file for the dates 01 December 18 to 30 November 2019




Figure 6. Sample ex.tif file for the dates 01 December 18 to 30 November 2019



Figure 7. Sample ey.tif file for the dates 01 December 18 to 30 November 2019

Velocities are reported in meters per year (m/yr). The vx and vy files contain component velocities in the x and y directions defined by the polar stereographic grid, EPSG 3413. These velocities are true values and not subject to the distance distortions present in a polar stereographic grid. Small gaps have been filled via interpolation in some areas. Interpolated values are identifiable as

locations that have velocity data but no error estimates. Radar-derived velocities are determined using a combination of conventional Interferometric SAR (InSAR) and speckle tracking techniques (Joughin et. al., 2002). The velocity magnitude, "vv", a scalar value, was calculated using the following forumula: $\sqrt{vx^2 + vy^2}$

1.1.2 Temporal Offset

The dT metric is the difference between the date for each velocity estimate and the midpoint date of the period measured. This metric can be used to measure temporal skew in the data.

The nominal time stamp for each mosaic is the midpoint date over the sampling period. So, in the case of the annual mosaics the midpoint is either May 31st or June 1st in a leap year. Due to the way the data are combined the time stamp is nominal rather than exact.

The dT for each point represents the number of days between the date for the velocity estimate for that point and the midpoint date of the annual measurement period. For example, if the mosaic covers the interval from 01 December 2014 to 30 November 2015, then the nominal midpoint date would be 31 May 2015, thus a value dT=5 for a point would indicate that 05 June better represents the midpoint for the data.

Although the averaged dT value provides some idea of the deviation from nominal date, **users** should be cautious when using dT to correct date. For more information regarding this topic, including how dT is calculated and its usage, refer to the Processing section.

1.1.3 Error Estimates

Error estimates represent the average behavior of the data and are provided for all non-interpolated, radar-derived velocity vectors in separate GeoTIFF files appended with <code>_ex.tif</code> and <code>_ey.tif</code>. Formal errors agree reasonably well with errors determined by comparison with GPS data (Joughin et al., 2002; Joughin et al., 2017). The values, however, underestimate true uncertainty in several ways, and as such should be used more as an indication of relative quality rather than absolute error. For more on error estimates, please refer to the section on Quality, Errors, and Limitations

1.1.4 Landsat 8 and Synthetic Aperture Radar Shapefiles

Shapefile ancillary files are provided for each data year to indicate the source image pairs that were processed to produce the mosaics. These are provided for the US Geological Survey (USGS)-provided Landsat 8 (L8s) and the German Aerospace Center (DLR) and European Space Agency (ESA)-provided Synthetic Aperture Radar (SAR) data.

1.1.5 Browse Files

JPG and GeoTIFF browse files provide an overview of the data. The files come in two resolutions, 200 m for TIFF and 500 m for the JPG files. In addition, there is an auxiliary file, .jpg.aux.xml, which provides projection information.




Figure 8. Sample browse.jpg file for the dates 01 December 18 to 30 November 2019

1.2 File Information

1.2.1 Format

Data are provided at 200 m resolution in cloud optimized GeoTIFF (.tif) format and at a 500 m resolution for the .jpg browse file. The GeoTIFFs were generated with GDAL 3.2.1 so the image statistics are written directly into the GeoTIFF file header. The statistical information for the 500 m .jpg browse files is stored in the accompanying .jpg.aux.xml files.

Velocity data files available for each data year and resolution include:

- velocity magnitude map (vv),
- separate x- and y-component velocities (vx, vy),
- separate x- and y-component error estimates (ex, ey),
- (dT) temporal offset; and
- 500 m resolution browse file in .tif format, and a browse file (with color log scale velocity saturating at 3000 m/year).

The LS8 and SAR data contain shapefiles used by most GIS software to geographically represent data. Shapefiles consist of a folder within which are several files all of the same name but with the following extensions: .dbf, prj, .shp, and .shx.

1.2.2 Naming Convention

This section explains the file naming convention used for this product with examples of the different file types. Refer to Table 1 for file name details. The general format for file names is as follows:

Product_startdate_enddate_parameter_version_filetype

Table 1. File Naming Conventions

File Name Component	GeoTiff	JPEG	Shapefile		
Product	GL_vel_mosaic_Annua	al; Greenland Annual Ice Shee SAR and Landsat	t Velocity Mosaics from		
Start date	Date of first	image used in mosaic period	n mosaic period (DDMonYY)		
End date	Date of last	image used in mosaic period	age used in mosaic period (DDMonYY)		
Parameter	Velocity Parameters dT: Temporal offset ex: x-axis error ey: y-axis error vv: velocity vx: x-axis velocity vy: y-axis velocity browse: vv browse image	browse: vv browse image	LS8: Landsat 8 SAR: Synthetic Aperture Radar		
v0#.#	Version number				
.ext	.tif; File extension, cloud optimized GeoTIFF; (raster)	.jpg (raster) .jpg. aux.xml (auxiliary file containing GDAL generated image statistics)	Shapefiles consisting of four files with extensions: .dbf the database file .prj (projection information) .shp (shapes) .shx (shape indices)		

1.2.3 Example File Names

1.2.3.1 Velocity Files

GL_vel_mosaic_Annual_01Dec18_30Nov19_dT_v03.0.tif

```
GL_vel_mosaic_Annual_01Dec18_30Nov19_ex_v03.0.tif
GL_vel_mosaic_Annual_01Dec18_30Nov19_ey_v03.0.tif
GL_vel_mosaic_Annual_01Dec18_30Nov19_vv_v03.0.tif
GL_vel_mosaic_Annual_01Dec18_30Nov19_vx_v03.0.tif
GL_vel_mosaic_Annual_01Dec18_30Nov19_vy_v03.0.tif
```

1.2.3.2 Shapefiles

LS8

```
GL_vel_mosaic_Annual_01Dec18_30Nov19_LS8_v03.0.dbf
GL_vel_mosaic_Annual_01Dec18_30Nov19_LS8_v03.0.shp
GL_vel_mosaic_Annual_01Dec18_30Nov19_LS8_v03.0.shx
GL_vel_mosaic_Annual_01Dec18_30Nov19_LS8_v03.0.prj
```

SAR

```
GL_vel_mosaic_Annual_01Dec18_30Nov19_SAR_v03.0.dbf
GL_vel_mosaic_Annual_01Dec18_30Nov19_SAR_v03.0.shp
GL_vel_mosaic_Annual_01Dec18_30Nov19_SAR_v03.0.shx
GL_vel_mosaic_Annual_01Dec18_30Nov19_SAR_v03.0.prj
```

1.2.3.3 Browse Files

```
GL_vel_mosaic_Annual_01Dec18_30Nov19_browse_v03.0.jpg
GL_vel_mosaic_Annual_01Dec18_30Nov19_browse_v03.0.jpg.aux.xml
GL vel mosaic Annual 01Dec18 30Nov19 browse v03.0.tif
```

1.3 Spatial Information

1.3.1 Coverage

This data set spans the entire Greenland Ice Sheet, as noted by the coverage below:

Southernmost Latitude: 60° N Northernmost Latitude: 83° N Westernmost Longitude: 75° W Easternmost Longitude: 14° W

1.3.2 Resolution

The data are posted at a 200 m grid resolution, which should not be confused with the true "on the ground" resolution. These products are derived as spatially varying averages from source data with resolutions ranging from a few hundred m to 1.5 km, making it difficult to specify the resolution at any point. As some estimates are derived as the average of 30 or more individual measurements,

there is some degree of resolution enhancement such that the final resolution is better than that of the individual source products, but not well quantified.

For work requiring finer resolution, it may be preferable to use the individual DLR TerraSAR-X (TSX)/TanDEM-X (TDX) and USGS Landsat data if available (*MEaSUREs Greenland Ice Velocity:* Selected Glacier Site Velocity Maps from InSAR; MEaSUREs Greenland Ice Velocity: Selected Glacier Site Velocity Maps from Optical Images).

1.3.3 Geolocation

Velocity parameters are provided in a WGS 84 polar stereographic grid with a standard latitude of 70° N and rotation angle of -45° (sometimes specified as a longitude of 45° W). With this convention, the y-axis extends south from the North Pole along the 45° W meridian (EPSG:3413). The SAR and LS8 shapefiles are in EPSG 4326.

Table 2. Northern Hemisphere Projection Based on WGS 1984 (EPSG: 3413)

Geographic Coordinate System	WGS 84
Projected Coordinate System	WGS 84 / NSIDC Sea Ice Polar Stereographic North
Longitude of True Origin	-45
Latitude of True Origin	70
Scale factor at longitude of true origin	1
Datum	WGS 1984
Ellipsoid/spheroid	WGS 84
Units	meter
False Easting	0
False Northing	0
EPSG Code	3413
PROJ4 String	+proj=stere +lat_0=90 +lat_ts=70 +lon_0=-45 +k=1 +x_0=0 +y_0=0 +datum=WGS84 +units=m +no_defs
Reference	http://epsg.io/3413

Table 3. Geographic Coordinate System

Geographic Coordinate System	WGS 84
EPSG code	4326
PROJ4 string	+proj=longlat +datum=WGS84 +no_defs
Reference	http://epsg.io/4326

1.4 Temporal Information

1.4.1 Coverage

This data set provides annual velocity mosaics for the years 2015 to 2020. The actual year is broadly defined as 01 December of one year to 30 November of the next year. For example, the year 2015 is defined as 01 December 2014 to 30 November 2015.

1.4.2 Resolution

The temporal resolution equals one year.

2 DATA ACQUISITION AND PROCESSING

2.1 Acquisition

These image mosaics were produced from data acquired by European Space Agency (ESA) Copernicus Sentinel-1A and Sentinel-1B satellites and supplemented with DLR TSX/TDX data for coastal outlets. The data were acquired in either 12-day (through Sept 2016) or 6-day repeat cycles (October 2016 forward). In cases of missing acquisitions, the repeat periods may be longer (integer multiples of 6 or 12 days) for some of the image pairs. In addition, USGS's Landsat 8 velocities were merged with SAR data during periods when there was sufficient daylight.

2.1.1 Annual Variations in Data Acquisition

This section details variations in data acquisition for the given time frames.

- 2015 (Dec 1, 2014 Nov 30, 2015): Sentinel-1A data acquisitions began in 2015, but the
 acquisition rates were not as regular as later years. As a result, these data tend to be
 somewhat noisier than the 2016 data, particularly in the middle of the ice sheet. In addition,
 the sampling of coastal regions is more irregular (there are gaps in the temporal coverage
 where TSX/TDX data were not acquired by the satellite for a month or more), which
 reduces the averaging of seasonal variation.
- 2016 (Dec 1, 2015 Nov 30, 2016): For this year, the six Sentinel-1A tracks that image the
 majority of the Greenland coast were collected for almost every 12-day satellite repeat
 cycle. Beginning in October 2016, Sentinel-1B started acquiring data over Greenland in an
 orbit that lags Sentinel-1A by six days, providing better coverage and thus more
 correlations in the data. As a result, the accuracy for these mosaics is considerably better
 than the mosaics for 2015 for most regions.
- 2017 (Dec 1, 2016 Nov 30, 2017): These products are similar to the earlier 2015 and 2016 products. The major difference is that this is the first year that regular 6-day coverage occurred throughout the year, which should improve performance on fast moving glaciers. In addition, the Copernicus Sentinel mission improved coverage for the southern part of Greenland in mid-2017, so the results should be improved for areas south of 67.5 degrees.
- 2018 (Dec 1, 2017 Nov 30, 2018): These products follow the same specifications as the previous year's release, with the following minor differences: some data using a few

scenes from the COnstellation of small Satellites for the Mediterranean basin Observation (COSMOSSkyMed) were included; some of the glaciers which were monitored by TSX in past years are covered by other instruments during this year.

• 2019 (Dec 1, 2018 – Nov 30, 2019): See specifications for previous releases.

2.2 Processing

These annual mosaics were computed as averages of all available data at each point and weighted by their respective errors (Joughin, 2002). As such, they do not represent true annual averages. For example, in some places mid-summer may be weighted more heavily than mid-winter due to the seasonal availability of Landsat 8 data. In some regions, clouds or large snow accumulation events may also affect the seasonal distribution of the data. As a result, comparison of adjacent years at any location might produce differences that represent some degree of seasonal variation. Such differences should be small, particularly when examining trends over multiple years. Unlike earlier SAR acquisitions, Sentinel-1A and -1B provide crossing ascending and descending orbit data over much of the ice sheet. In areas where crossing-orbit data were available, an errorweighted range-offset-only solution was included in the velocity product. Where these data are included, the error are generally substantially lower than solutions with azimuth offsets, which can be subject to large errors due to ionospheric streaking. By virtue of the error weighting, the rangeoffset-only solutions tend to dominate the aggregate solution, to yield more accurate results. This product uses a variation of the GIMP DEM (NSIDC-0715). The variation has a lower resolution of 270 m and geoidal heights are used for the ocean. The DEM used in this Version (v03) also contains a correction to a 15m horizontal shift that was identified in the DEM used in the previous version of this product. See the blue box below for further details on the implications of this correction for users. Data have more robust error checking. Each estimate is compared against the statistics from the entire time series. Data are discarded if they exceed a threshold (e.g., 3sigma). The final products are also manually edited to remove obvious artifacts.

Note to Users: For version 3 of this product, an additional correction was made to the DEM to address a horizontal shift of 15 m identified in version 2 data, resulting in some changes to the data between version 2 and version 3. While in general the differences are minor (~< 1m/yr), very large differences (> 1000 m/yr) may occur at isolated pixels near steep calving fronts or other steep slopes. Points in these regions should always be treated with some degree of caution. Even with these extreme outliers, the root-mean-square differences are < 2 m/yr for the entire map.

2.3 Baseline Fits

Each image pair used in the mosaic requires a 4- to 6-parameter fit for the baseline parameters. The data are fit to a common set of ground control points as described by Joughin et al. (2010). For years where data is not well controlled (sparse ground control points), control points from other

years with adequate controls are used. This greatly improves consistency of the data from year to year. While this could mask some true change, the errors without this procedure are far larger than any change likely to occur.

These data should not be used to determine inter-annual change for interior regions of the ice sheet (roughly defined as areas above 2,000 m). In outlet glaciers close to the coast where the baselines are well constrained by bedrock, the velocity mosaics are well suited to this task. However, care should be exercised in interpreting any change observed in intermediate regions (roughly 1000 m to 2000 m), i.e., avoid areas where the observed changes seem to follow a satellite swath boundary. Refer to Figure 5 in Phillips et al., (2013) for an example.

2.3.1 Aggregation and Weighting

For each year, all available data are aggregated and combined in an error-weighted method to achieve an optimal estimate with respect to error reduction. Due to limited coverage or lack of unsuccessful matches, there are data gaps such that the full annual period may not be sampled uniformly.

2.3.2 Temporal Offset Calculation

It is recommended that the dT parameter is used to flag potential time-skew issues, and that it is not used for date correction. As a result of the data aggregation process, the true date represented by the data may differ from the nominal midpoint date of the mosaic period.

As a measure of temporal skew, the mean deviation, dT, was calculated from the midpoint date in days for each point. This metric is calculated by applying the same weighting to the difference between the date for each velocity estimate and the midpoint date, and then weighted using the same methods as the velocity data. In estimating velocity, different weights are used for the vx and vy components, so an intermediate weight is used for the individual dTs. In the final mosaicking step, any data with dT greater than one-half the output interval was discarded. As a result, for the annual product, the time stamp error is less than or equal to approximately 183 days.

In more detail, the process for calculating dT follows these steps:

- 1. Using a Day of the Year (DOY) calendar, determine the midpoint for the measurement period i.e., quarterly, monthly or annual.
- 2. For each pixel identify the image pairs used as input for velocity and calculate the central date in terms of the DOY.
- 3. Calculate a weighted average central date for that pixel using an intermediate weight based on the weights used for the vx and vy components.
- 4. dT = weighted average central date midpoint.

Although the averaged dT value provides some idea of the deviation from nominal date, users should be cautious when using dT to correct dates. For example, if the mosaic covers the period

from 01 December 2014 to 30 November 2015, the nominal midpoint would be 31 May 2015, thus a value dT=5 would indicate that 05 June better represents the midpoint. However, there are convoluted cases that could also result in a dT=5. For examples of complex or convoluted cases, please refer to section 2.2.3 of the User Guide for NSIDC-0727, MEaSUREs Greenland Quarterly Ice Velocity Mosaics from SAR and Landsat.

The use of dT to flag potential time skew issues is recommended, rather than for date correction. If a large temporal skew is identified, the use of other GIMP products with finer temporal sampling is recommended to analyze the temporally varying behavior.

2.3.3 Potential Artifacts

The data are posted to 200 m grid; however, the true resolution varies between a few hundred m to 1.5 km. Posting represents the spacing between samples and should not be confused with the resolution at which the data were collected. Many small glaciers are resolved outside the main ice sheet, but for narrow (<1 km) glaciers, the velocity represents an average of both moving ice and stationary rock. As a result, while the glacier may be visible in the map, the actual speed may be underestimated. For smaller glaciers, interpolation produces artifacts where the interpolated value is derived from nearby rock, causing apparent stationary regions in the middle of otherwise active flow. The data have been screened to remove most of these artifacts, but should be used with caution.

2.3.4 Interpolated Points

Small gaps in the final maps have been filled via interpolation. These points can be identified as those that have valid velocity data but no corresponding error estimate. See Joughin et al. (2002) for more detail on errors and how they were computed.

2.3.5 Areas with No Data

Areas with no data correspond either to regions where no data were acquired or where the interferometric or optical correlation was insufficient to produce an estimate. This occurs most often in areas with high snow accumulation. The no data value for vv, ex, and ey files is -1. The no data value for vx, vy and dT is -2e9.

2.3.6 Geometric Terrain Correction

The mosaics in this data set were geometrically terrain-corrected with modified version of MEaSUREs Greenland Ice Mapping Project (GIMP) Digital Elevation Model from GeoEye and WorldView Imagery, Version 1. The modified version of the DEM differed from the published one in that it used geoidal heights for the ocean and has a resolution of 270 m. Additionally, a correction

was made to the modified DEM to address a 15 m horizontal shift identified in the previous, version 2, data set. See section 2.2, note to users for additional information.

2.3.7 GDAL-Generated Cloud Optimized GeoTIFFs

The GeoTIFFs were generated using Geospatial Data Abstraction Library (GDAL) 3.2.1 to make them compatible with the latest cloud optimized GeoTIFF format. GDAL generates previews for Cloud Optimized GeoTIFFs and the default is to use cubic interpolation, but this results in minor artifacts around the lower resolution previews. Therefore, averaging is used instead to avoid this issue and aliasing. Also, this version of GDAL writes the image statistics directly to the file header.

2.4 Quality, Errors, and Limitations

Due to the large volume of averaged source data, the overall quality of the data set is quite good. While the spatial coverage is generally improved in the southeast relative to earlier Greenland Ice Mapping Project (GIMP) MEaSUREs products, the results are considerably noisy relative to other regions of the ice sheet. High snow accumulation in the southeast greatly reduces image-to-image correlation, resulting in higher noise. Additionally, in these regions there may be coherent displacement signals (e.g., vertical displacement associated with compacting snow) that are not associated with horizontal ice motion. If such displacement occurs with characteristics other than that assumed in the solution (e.g., predominantly vertical instead of horizontal displacement), then the results will be incorrectly mapped to horizontal motion, thereby contributing to the overall level of noise.

Error estimates are provided for all non-interpolated, radar-derived velocity vectors in separate GeoTIFF files appended with <code>_ex.tif</code> and <code>_ey.tif</code>. Formal errors agree reasonably well with errors determined by comparison with GPS data (Joughin et al., 2002; Joughin et al., 2017). The values, however, underestimate true uncertainty in several ways, and as such, should be used more as an indication of relative quality rather than absolute error.

In general, the error estimates represent the average behavior of the data. This means that errors may be much lower than reported in some areas and much greater in others; care should be taken if assigning statistical significance based on the errors, especially given that the errors can be been correlated over large areas. For example, even if the errors are correct in a global sense, one might compare two mosaics and find a large difference over 5% of the ice sheet. However, because errors can be spatially correlated over broad areas, one should not assume significance at the 95% confidence level; this might be precisely the 5% that statistically should exceed the errors because the errors are not uniformly distributed. By contrast, if the errors were completely uncorrelated, one could average over neighborhoods to reduce the error.

2.5 Instrumentation

2.5.1 Description

Descriptions of the instruments used to construct the mosaics from which this data set is derived are at the mission sites:

- European Space Agency (ESA): Copernicus Sentinel-1
- German Aerospace Center (DLR): TerraSAR-X (TSX) and TanDEM-X (TDX)
- US Geological Survey (USGS): Landsat 8

3 SOFTWARE AND TOOLS

GeoTIFF files and shapefiles can be viewed with a variety of Geographical Information System (GIS) software packages including QGIS and ArcGIS.

4 VERSION HISTORY

Table 4. Version History Summary

Version	Release Date	Description of Changes
1.0	October 2017	Initial release
	April 2020	This data set was first published in October 2017, with annual updates thereafter. In April 2020 the data access location was changed, leading to renaming of all data files to conform to the version-numbering standard.

Version	Release Date	Description of Changes
2.0	February 2020	 The following list summarizes changes: New file naming convention. Data set temporal range increased by one year from: 01 December 2014 to 30 November 2019. Application of a new DEM, NSIDC-0715; prior versions relied on NSIDC-0645 Addition of dT GeoTIFFs, a temporal offset parameter. All files have a 200 m resolution with the exception of the browse.jpg which is at 500 m; 500 m resolution velocity files no longer available A more rigorous culling of the data removed bad data and added previously overlooked data. As a result, mosaics show more areas with no data, the min/max ex and ey values are lower, and SAR/LS8 feature counts differ from Version 1. The no data value for vv changed from -0.1 to -1; the no data value for ex and ey changed from -2e9 to -1. Newly available are cloudoptimized GeoTIFFs along with tif.aux.xml, and jpg.aux.xml files
3.0	June 2021	This version update includes: Use of GDAL 3.2.1 to create cloud optimized GeoTIFFs Update of temporal coverage Data reprocessed utilizing a corrected DEM. See user note in section 2.2

5 RELATED DATA SETS

- MEaSUREs Greenland Quarterly Ice Sheet Velocity Mosaics from SAR and Landsat
- MEaSUREs Greenland Monthly Ice Sheet Velocity Mosaics from SAR and Landsat
- MEaSUREs Greenland Ice Velocity: Selected Glacier Site Velocity Maps from InSAR
- MEaSUREs Greenland Ice Sheet Velocity Map from InSAR Data

6 RELATED WEBSITES

- MEaSUREs Data | Overview
- Alaska Satellite Facility
- Greenland Ice Mapping Project (GIMP)

7 CONTACTS AND ACKNOWLEDGMENTS

Ian Joughin

University of Washington Applied Physics Laboratory

Acknowledgements

This project was supported by a grant from the NASA Making Earth System Data Records for Use in Research Environments (MEaSUREs) Program.

Contains modified Copernicus Sentinel data (2014-2016), acquired by the ESA, distributed through the Alaska Satellite Facility, processed by Joughin, I. and from the TanDEM-X and TerraSAR-X missions processed by DLR, as well as results derived from optical images collected by Landsat-8 processed by USGS.

8 REFERENCES

Joughin, I. (1995). Estimation of ice-sheet topography and motion using interferometric synthetic aperture radar. *PhD Dissertation*, University of Washington.

Joughin, I. (2002). Ice-sheet velocity mapping: a combined interferometric and speckle-tracking approach. *Annals of Glaciology*, 34, 195–201. https://doi.org/10.3189/172756402781817978

Joughin, I., Tulaczyk, S., Bindschadler, R., & Price, S. F. (2002). Changes in west Antarctic ice stream velocities: Observation and analysis. *Journal of Geophysical Research: Solid Earth*, 107(B11), EPM 3-1-EPM 3-22. https://doi.org/10.1029/2001jb001029

Joughin, I., Abdalati, W., & Fahnestock, M. (2004). Large fluctuations in speed on Greenland's Jakobshavn Isbræ glacier. Nature, 432(7017), 608–610. https://doi.org/10.1038/nature03130

Joughin, I., Smith, B. E., Howat, I. M., Scambos, T., & Moon, T. (2010). Greenland flow variability from ice-sheet-wide velocity mapping. *Journal of Glaciology*, 56(197), 415–430. https://doi.org/10.3189/002214310792447734

Joughin, I., Smith, B. E., & Howat, I. M. (2017). A complete map of Greenland ice velocity derived from satellite data collected over 20 years. *Journal of Glaciology*, 64(243), 1–11. https://doi.org/10.1017/jog.2017.73

Moon, T., & Joughin, I. (2008). Changes in ice front position on Greenland's outlet glaciers from 1992 to 2007. *Journal of Geophysical Research*, 113(F2). https://doi.org/10.1029/2007jf000927

Phillips, T., Rajaram, H., Colgan, W., Steffen, K., & Abdalati, W. (2013). Evaluation of cryohydrologic warming as an explanation for increased ice velocities in the wet snow zone, Sermeq Avannarleq, West Greenland. *Journal of Geophysical Research*: Earth Surface, 118(3), 1241–1256. https://doi.org/10.1002/jgrf.20079

Rignot, E. (2006). Changes in the Velocity Structure of the Greenland Ice Sheet. *Science*, 311(5763), 986–990. https://doi.org/10.1126/science.1121381

9 DOCUMENT INFORMATION

9.1 Publication Date

20 March 2020

9.2 Date Last Updated

23 June 2021