



IceBridge KT19 IR Surface Temperature, Version 2

USER GUIDE

How to Cite These Data

As a condition of using these data, you must include a citation:

M. Studinger. 2020. *IceBridge KT19 IR Surface Temperature, Version 2*. [Indicate subset used].
Boulder, Colorado USA. NASA National Snow and Ice Data Center Distributed Active Archive Center.
<https://doi.org/10.5067/UHE07J35I3NB>. [Date Accessed].

FOR QUESTIONS ABOUT THESE DATA, CONTACT NSIDC@NSIDC.ORG

FOR CURRENT INFORMATION, VISIT <https://nsidc.org/data/IAKST1B>



National Snow and Ice Data Center

TABLE OF CONTENTS

1	DATA DESCRIPTION	2
1.1	Parameters	2
1.2	File Information.....	2
1.2.1	Format.....	2
1.2.2	File Contents.....	2
1.2.3	Naming Convention	3
1.3	Spatial Information.....	3
1.3.1	Coverage	3
1.3.2	Resolution.....	4
1.3.3	Geolocation.....	4
1.4	Temporal Information	4
1.4.1	Coverage	4
1.4.2	Resolution.....	4
2	DATA ACQUISITION AND PROCESSING.....	5
2.1	Instrumentation.....	5
2.2	Acquisition	5
2.3	Processing.....	6
2.4	Errors and Limitations.....	6
3	SOFTWARE AND TOOLS	6
4	VERSION HISTORY	6
5	RELATED DATA SETS.....	7
6	RELATED WEBSITES	7
7	CONTACTS.....	7
8	ACKNOWLEDGMENTS.....	7
9	DOCUMENT INFORMATION.....	7
9.1	Publication Date	7
9.2	Date Last Updated.....	7

1 DATA DESCRIPTION

1.1 Parameters

The KT19.85 sensor provides a measurement of the surface temperature of an object in degrees Celsius. For compensation purposes, the sensor also provides a measurement of its internal temperature, in degrees Celsius, which may vary as much as 30°C throughout the course of a flight. The surface temperature measurement provided has not had any correction applied for changes in internal temperature.

1.2 File Information

1.2.1 Format

The KT19 data files are in ASCII text format with each row of the file corresponding to a separate measurement record. Each data file is paired with an associated XML file, which contains additional metadata.

1.2.2 File Contents

Each row of the KT19 ASCII data file corresponds to a separate measurement record. The data file contains eight columns of data, with each column corresponding to a different variable describing the measurement, as shown in Table 1.

The files also contain a number of header lines beginning with a hashtag (#) and containing the settings used for acquisition (emissivity, response time, temperature units, etc.). The last header line describes the information found in each column of the data.

Table 1. Parameter Description

Parameter	Description	Units
Year	Year of measurement	Years
Day_Of_Year	Day of year of measurement	Days
Seconds_Of_Day	Seconds of day of measurement (UTC)	Seconds
Latitude	Latitude of GPS antenna	Decimal degrees
Longitude	Longitude of GPS antenna	Decimal degrees
Aircraft_Altitude_Above_Ellipsoid	Height of GPS antenna above WGS84 ellipsoid	Meters

Parameter	Description	Units
KT19_Temperature	Surface temperature measured by the KT19	Degrees Celsius
KT19_Internal_Temperature	KT19 instrument internal temperature	Degrees Celsius

1.2.3 Naming Convention

Example file names:

IAKST1B_KT19_PROCESSED_20190517_093051.txt

IAKST1B_KT19_PROCESSED_20190517_093051.txt.xml

Files are named according to the following convention, which is described in more detail in Table 2:

IAKST1B_KT19_PROCESSED_YYYYMMDD_hhmmss.xxx

Table 2. File Naming Convention

Variable	Description
IAKST1B	Data set ID
KT19_PROCESSED	KT19 Level-1B processed data file
YYYY	Four-digit year of survey
MM	Two-digit month of survey
DD	Two-digit day of survey
hh	Two-digit hour for start of log file
mm	Two-digit minute for start of log file
ss	Two-digit second for start of log file
.xxx	Indicates ASCII text file (.txt), or xml file (.txt.xml)

All dates and times included in the filenames are based on machine local time.

1.3 Spatial Information

1.3.1 Coverage

Spatial coverage includes Arctic and Antarctic sea and land ice.

Arctic / Greenland:

Southernmost Latitude: 60° N

Northernmost Latitude: 90° N

Westernmost Longitude: 180° W

Easternmost Longitude: 180° E

Antarctic:

Southernmost Latitude: 90° S

Northernmost Latitude: 53° S

Westernmost Longitude: 180° W

Easternmost Longitude: 180° E

1.3.2 Resolution

The KT19 sensor is fitted with a lens that has a two-degree field of view. At 450 m above ground level, this produces an optical measurement footprint on the ground that is approximately 15 m in diameter. At a nominal aircraft speed of 125 m/s and a sampling frequency of 10 Hz, the centers of two consecutive spots will be 12.5 m apart along the aircraft ground track.

1.3.3 Geolocation

The KT19 data incorporate a GPS location that is referenced to the WGS 84 datum.

1.4 Temporal Information

1.4.1 Coverage

05 March 2012 to 17 May 2019

1.4.2 Resolution

IceBridge campaigns are conducted on an annually repeating basis. Arctic and Greenland campaigns are typically conducted during March, April, and May; Antarctic campaigns are typically conducted during October and November.

KT19 surface temperature measurements are collected for every science flight in the NASA IceBridge Arctic campaigns, with Version 2 of the data beginning on 05 March 2012. The KT19 collects surface temperature measurements at 10 Hz for the duration of each flight.

Note: Data collected on 05 and 06 March 2012 are from test flights.

2 DATA ACQUISITION AND PROCESSING

2.1 Instrumentation

The Heitronics KT19 Infrared Radiation Pyrometer measures infrared radiation wavelengths between 9.6 and 11.5 microns.

For all Arctic and Antarctic campaign data, the emissivity constant was set to 0.97. By assuming an emissivity of 0.97, a reasonable estimate for most sea and land ice, the radiation measurement can be directly converted to a measurement of the target's surface temperature. The KT19.85 model is designed for long-distance measurement of water, ice, and clouds, and has an effective measurement range from -50°C to 200°C , with a resolution of 0.01°C . The lens has a two-degree field of view, which yields a 15 m viewing footprint on the ground at 450 m above ground level. The response time of the KT19 detector is nominally set to 0.3 s to provide a good balance between measurement sensitivity and noise reduction for a measurement frequency of 10 Hz. For instrument accuracy and other instrument specifications, see the Wintronics KT19 Series II Infrared Thermometer website.

2.2 Acquisition

Data collection for the KT19 data takes place on a CappuccinoPC mini-PC running Ubuntu 10.4. The computer communicates with the KT19 sensor over the RS-232 interface and with a GPS-logging computer over Ethernet. The combination of these two data streams provides geolocated surface temperature measurements.

The collection and logging of the KT19 data is managed by a python script called `KTlogger.py`. After the KT19 sensor is powered on, the script issues initialization commands to the sensor to set the temperature units, response time, reference temperature method, and emissivity constant. After that, the script begins the data collection loop, which queries the KT19 sensor at 10 Hz for the surface temperature, and at 0.5 Hz for internal temperature. This script also communicates with a separate GPS logging machine onboard the ATM GPS rack, which is running a program called `linlogger`. The `linlogger` program broadcasts a real-time GPS message over Ethernet at 2 Hz. All of the messages returned from the KT19, as well as the real-time GPS messages, are time stamped with machine local time and written to a log file as they arrive.

2.3 Processing

A processing script called `KTproc.py` loads in all of the collected data from a flight and linearly interpolates the measurements to the frequency at which the KT19 surface measurements were collected. The interpolation uses the machine local time stamp as the independent variable.

2.4 Errors and Limitations

On a few flights, the KT19.85 sensor would return an empty string when queried for a temperature measurement. As soon as the operator identified this error, the data file would be closed, power would be cycled to the sensor, and a new data file started. Therefore, some flights have more than one data file.

The Heitronics KT19 Infrared Radiation Pyrometer is a nadir-viewing optical instrument, so it will measure the temperature of the first surface that appears below the aircraft. As long as no clouds are between the aircraft and the ice below, the surface measurement will correspond to the ice surface. However, if any clouds appear between the aircraft and the ice surface, then the KT19 temperature measurement will correspond to the cloud temperature. The KT19 data set does not contain any information about the presence of clouds. A secondary data set, such as *IceBridge DMS L1B Geolocated and Orthorectified Images* or *IceBridge CAMBOT L1B Geolocated Images*, can be used to identify the objects that were measured by the KT19.

3 SOFTWARE AND TOOLS

The data files may be opened using any software capable of reading ASCII text data.

4 VERSION HISTORY

Table 3 provides a version history for this data set.

Table 3. Version History

Version Number	Time Frame	Description
1	12 October 2011 to 17 May 2019	Initial release
2	05 March 2012 to 17 May 2019	Improvement of the geolocation of the KT-19 footprints, due to replacing the coarse real-time GPS positions with post-processed differential GPS positions. The post-processed trajectories are the same as used for the ATM lidar processing.

5 RELATED DATA SETS

[IceBridge KT19 IR Surface Temperature, Version 1](#)
[IceBridge CAMBOT L1B Geolocated Images](#)
[IceBridge DMS L1B Geolocated and Orthorectified Images](#)

6 RELATED WEBSITES

[Wintronics KT19 Series II Infrared Thermometer website](#)
[IceBridge data website at NSIDC](#)
[IceBridge website at NASA](#)

7 CONTACTS

Michael Studinger

Cryospheric Sciences Laboratory
NASA Goddard Space Flight Center
Greenbelt, Maryland, USA

8 ACKNOWLEDGMENTS

The ATM project team would like to acknowledge the dedicated NASA P-3 flight crew, whose efforts allowed the safe and efficient collection of this data over some of the most isolated and extreme regions on this planet.

9 DOCUMENT INFORMATION

9.1 Publication Date

10 December 2020

9.2 Date Last Updated

10 December 2020